Teron Lighting

ARCHITECTURAL OUTDOOR

ROYAL EB TEB

PROJECT:	
TYPE:	
ORDERING # :	
COMMENTS:	

COMPACT FLUORESCENT

FEATURES

- Steel Fascia w/ Textured Black Polyester Powder Coat Finish
- Luminous White 75% DR Acrylic Diffuser
- Steel Mounting Pan w/ Hi-Reflectance White Powder Coat Finish
- Mounts Directly to 4" Junction Box (By Others)
- Mounting Hardware Included
- Lamps Included
- Wet Location
- Integral EM Battery Available

ORDERING INFORMATION

Example : (RLB - TEB - 232X - 120E - SN - 27K) **Textured Black is Standard Finish**

RLB

PRODUCT	SOURCE/WATTAGE	VOLTAGE	DIFFUSER	FINISH	OPTIONS
Royal EB	**TEB-226Q** - (2) 26W QE **TEB-227E** - (2) 27W 4-Pin Biax **TEB-232X** - (2) 32W TBX **TEB-239E** - (2) 39W 4-Pin Biax	**120E** - Electronic **277E** - Electronic	**Not Applicable**	**SM** - Matte Silver **TB** - Textured Black **AC** - Antique Copper **AS** - Antique Silver **BT** - Bronze Mist **CP** - Copper **SN** - Sand **SW** - Swedish Steel **BZ** - Textured Bronze **TW** - Textured White **RAL Colors or Custom Match - Consult Factory**	**41K** - 4100K Color Temp. (Standard) **35K** - 3500K Color Temp. **30K** - 3000K Color Temp. **27K** - 2700K Color Temp. (Not Available in 4-Pin Biax) **F** - Fused **DIM** - Dimming Ballast **EBR** - Remote Mount Battery (Field Installed)* **EBW / EBC**- Integral Emergency Battery* **W2L** - Wire 2 Lamps to Integral Emergency Battery (2x26W Maximum) **MSP** - Program Start Ballast (Recommended for Motion Sensor) ***

REPLACEMENT PARTS — PART NO.

White 75% DR Acrylic Lens	3051160

We reserve the right to revise the design or components of any product due to parts availability or change in UL standards, without assuming any obligation or liability to modify any products previously manufactured, and without notice.

NOTES

***Emergency Battery Options**

Initial light output in Emergency mode will last for a minimum of 90 minutes. 1 lamp wired unless ordered otherwise. The following are suitable for indoor and damp locations. Please refer to Bodine's specification sheet

EBR:

Bodine's B94CG (Electronic) - Temperature Rating (Ambient) 32° F - 122° F

EBW:

Bodine's B94G (Electronic) - Temperature Rating (Ambient) 32° F - 131° F

EBC:

Bodine's B4CF1 (Electronic) - Temperature Rating (Ambient) -4° F - 131° F

*** For Electronic Wattage Fixtures Being Used in Conjunction With an Occupancy Sensor (Either Provided by us, or Your Own System), a Program Start Ballast is Recommended in Order to Maximize Lamp Life.

ARRA 2009

BUY AMERICA ACT

INTEGRAL BATTERY AVAILABLE

33 DONALD DRIVE FAIRFIELD, OH 45014 PH:(513)858-6004 FAX:(513)858-6038 EMAIL:SALES@TERONLIGHT.COM WEB:TERONLIGHT.COM