Teron Lighting

ARCHITECTURAL INDOOR

NIKE C

COMPACT FLUORESCENT

PROJECT:

TYPE:

ORDERING # :

COMMENTS:

FEATURES

- Die-Form Cold-Rolled Steel Housing w/ Brushed Nickel Plated Finish
- Steel Trim w/ Brushed Nickel Plated Finish
- Steel Mounting Pan w/ Hi-Reflectance White Powder Coat Finish
- Luminous White Acrylic Diffuser
- Mounts Directly to 4" Junction Box (By Others)
- Mounting Hardware Included
- Lamps Included
- 14 1/2" Housing is ADA Compliant
- CSA Listed Damp Location For United States of America Only





ORDERING INFORMATION

Example : (NEC213Q - 120E - 27K) **Brushed Nickel is Standard Finish**

PRODUCT	SOURCE/WATTAGE	VOLTAGE	DIFFUSER	FINISH	OPTIONS
Nike C **14 1/2" Housing**	**NEC14-213Q** - (2) 13W QE ** **NEC14-218Q** - (2) 18W QE ** **NEC14-122CE** - (1) 22W T5 Circ **NEC14-226Q** - (2) 26W QE	**120E** - 120V Electronic **277E** - 277V Electronic **347E** - 347V Electronic	**Not Applicable**	**BN** - Brushed Nickel Plate **SM** - Matte Silver **TB** - Textured Black **AC** - Antique Copper **AS** - Antique Silver **BT** - Bronze Mist **CP** - Copper **KC** - Kenworth Chrome **SN** - Sand **SW** - Swedish Steel **BZ** - Textured Bronze **TW** - Textured White **RAL Colors or Custom Match - Consult Factory**	**41K** - 4100K Color Temp. (Not Available For T5 Circ) **35K** - 3500K Color Temp. **30K** - 3000K Color Temp. **27K** - 2700K Color Temp. (Not Available for T5 Circ) **DIM** - Dimming Ballast ** (2 Lamp QE Electronic Only) (Not Available For 2x26W on NEC14) **EBR** - Remote Mount Battery (Field Installed)* **MSP** - Program Start Ballast (Recommended for Motion Sensor) ***
Nike C **17 3/4" Housing**	**NEC18-226Q** - (2) 26W QE ** **NEC18-313Q** - (3) 13W QE **NEC18-318Q** - (3) 18W QE **NEC18-326Q** - (3) 26W QE **NEC18-140CE** - (1) 40W T5 Circ **NEC18-162CE** - (1) 22W & 40W T5 Circ **Fixtures With a ** Are Available With a Dimming Option**				

REPLACEMENT PARTS	PART NO.
14" White Acrylic Diffuser	3049660
18" White Acrylic Diffuser	3049760

We reserve the right to revise the design or components of any product due to parts availability or change in UL standards, without assuming any obligation or liability to modify any products previously manufactured, and without notice.

NOTES

***Emergency Battery Options**

Initial light output in Emergency mode will last for a minimum of 90 minutes. 1 lamp wired unless ordered otherwise. The following are suitable for indoor and damp locations. Please refer to Bodine's specification sheet

EBR:

Bodine's B94CG (Electronic) - Temperature Rating (Ambient) 32° F - 122° F

ARRA 2009

BUY AMERICA ACT

US

ADA Compliant

*** For Electronic Wattage Fixtures Being Used in Conjunction With an Occupancy Sensor (Either Provided by us, or Your Own System), a Program Start Ballast is Recommended in Order to Maximize Lamp Life.

33 DONALD DRIVE FAIRFIELD, OH 45014 PH:(513)858-6004 FAX:(513)858-6038 EMAIL:SALES@TERONLIGHT.COM WEB:TERONLIGHT.COM