

ARCHITECTURAL OUTDOOR

## BRONZE CUP MD





COMPACT FLUORESCENT & HID

PROJECT :
TYPE :
ORDERING # :
COMMENTS :

### FEATURES

- Cast Aluminum Housing w/ Textured Bronze Polyester Powder Coat Finish
- Clear Prismatic Borosilicate Glass Lens
- Fully Gasketed
- Stainless Steel Zinc-Coated Screws
- Mounts Direct to Flat Surface w/ Four #8 Wall Anchors (Not Included)
- Cast-In Template
- Lamps Included
- Integral EM Battery Available
- CSA Listed For Wall Mounting



**0.50" Conduit Entries**  
**One Each on Opposite Sides, One On Top, and One On Back of Housing**

### ORDERING INFORMATION

Example : (BPM50MH - 120H)

Textured Bronze is Standard Finish

PRODUCT	SOURCE/WATTAGE	VOLTAGE	DIFFUSER	FINISH	OPTIONS
Bronze Cup Md	<b>BPM50MH</b> - 50W MH <b>BPM70MH</b> - 70W MH <b>BPM100MH</b> - 100W MH  <b>BPM50</b> - 50W HPS <b>BPM70</b> - 70W HPS <b>BPM100</b> - 100W HPS  <b>BPM132X</b> - (1) 32W TBX <b>BPM142X</b> - (1) 42W TBX <b>BPM226X</b> - (2) 26W TBX <b>BPM232X</b> - (2) 32W TBX	<u>METAL HALIDE (MH)</u> <b>120V</b> - 120V HPF <b>120H</b> - MT HPF (Wired 120V) <b>MTH</b> - MT HPF (Wired 277V) <b>347H</b> - MT HPF (Wired 347V)  <u>HPS</u> <b>120V</b> - 120V HPF <b>120H</b> - MT HPF (Wired 120V) <b>MTH</b> - MT HPF (Wired 277V)  (MT - Multi-Tap)  <u>FLUORESCENT (F)</u> <b>120E</b> - 120V Electronic <b>277E</b> - 277V Electronic	Not Applicable	<b>SM</b> - Matte Silver <b>TB</b> - Textured Black <b>AC</b> - Antique Copper <b>AS</b> - Antique Silver <b>BT</b> - Bronze Mist <b>CP</b> - Copper <b>SN</b> - Sand <b>SW</b> - Swedish Steel <b>BZ</b> - Textured Bronze <b>TW</b> - Textured White  <b>RAL Colors or Custom Match - Consult Factory</b>	<b>41K</b> - 4100K Color Temp.* <b>35K</b> - 3500K Color Temp.* <b>30K</b> - 3000K Color Temp.* <b>27K</b> - 2700K Color Temp.* (Standard) <b>F</b> - Fused <b>PCL120</b> - Photocell 120V <b>PCL277</b> - Photocell 277V <b>DIM</b> - Dimming Ballast * (Electronic Only) <b>QRS</b> - Quartz Restrike (DC/Bay - Lamp Included) <b>QZS</b> - Quartz Socket Only <b>EBW / EBC</b> - Integral Emergency Battery** (Electronic Only) <b>EBR</b> - Remote Mount Battery (Field Installed) ** <b>VS</b> - Dark Sky Visor (Field Installed) <b>W2L</b> - Wire 2 Lamps to Integral Emergency Battery (EBW Only) (2x18W Maximum) <b>MSP</b> - Program Start Ballast (Recommended for Motion Sensor) ***

### REPLACEMENT PARTS

### PART NO.

Clear Tempered Glass Diffuser	37033
Dark Sky Visor (Please Specify Color When Ordering) (Must Order Separately)	5301999

We reserve the right to revise the design or components of any product due to parts availability or change in UL standards, without assuming any obligation or liability to modify any products previously manufactured, and without notice.

ARRA 2009



BUY AMERICA ACT

### NOTES

**\*Fluorescent Only**

**\*\*Emergency Battery Options**

Initial light output in Emergency mode will last for a minimum of 90 minutes. 1 lamp wired unless ordered otherwise. The following are suitable for indoor and damp locations. Please refer to Bodine's specification sheet

- EBW:** Bodine's B94G (Electronic) - Temperature Rating (Ambient) 32° F - 131° F
- EBC:** Bodine's B4CF1 (Electronic) - Temperature Rating (Ambient) -4° F - 131° F
- EBR:** Bodine's B94CG (Electronic) - Temperature Rating (Ambient) 32° F - 122° F

\*\*\* For Electronic Wattage Fixtures Being Used in Conjunction With an Occupancy Sensor (Either Provided by us, or Your Own System), a Program Start Ballast is Recommended in Order to Maximize Lamp Life.