

PROJECT :
TYPE :
ORDERING # :
COMMENTS :

**BIRDIE CA**




COMPACT FLUORESCENT



**FEATURES**

- Die-Cast Aluminum Housing w/ Matte White Polyester Powder Coat Finish
- Die-Cast Aluminum Grill (Standard) w/ Matte White Polyester Powder Coat Finish
- Frosted Ribbed Borosilicate Glass Lens
- Front & Back Gasketing
- Stainless Steel Housing Screws
- Mounts Directly to 4" Junction Box (By Others)
- Mounting Hardware Included
- Lamps Included
- Integral EM Battery Available (Damp Location Only)  
(1x13W & 1x18W Only For CSA Compliance)
- CSA Listed Wet Location For Ceiling Mount up to 1x42W, Including PCL Option
- CSA Listed Wet Location For Wall Mount up to 2x26W, Including PCL Option
- CSA Listed Wet Location For Wall Mount up to 1x18W When Both EB & PCL Options Are Used


Optional Eye  
**EYE**



Optional Ring  
**RNG**



Standard Grill  
**GRL**



**ORDERING INFORMATION**

Example : (BEC213Q - 120E - GRL - SN - 41K)

Matte White is Standard Finish

PRODUCT	SOURCE/WATTAGE	VOLTAGE	FASCIA	FINISH	OPTIONS
Birdie CA	BEC113Q - (1) 13W QE ** BEC213Q - (2) 13W QE BEC118Q - (1) 18W QE ** BEC218Q - (2) 18W QE BEC126X - (1) 26W TBX BEC226X - (2) 26W TBX BEC132X - (1) 32W TBX BEC142X - (1) 42W TBX BEC100A19 - (1) 100W Incandescent  ** CSA Approved For EB (Wall Mount Only)	120E - Electronic 120V 277E - Electronic 277V	GRL - Birdie Grill (Standard) EYE - Birdie Eye RNG - Birdie Ring	WH - Matte White (Standard) SM - Matte Silver TB - Textured Black AC - Antique Copper AS - Antique Silver BT - Bronze Mist CP - Copper SN - Sand SW - Swedish Steel BZ - Textured Bronze TW - Textured White  RAL Colors or Custom Match - Consult Factory	41K - 4100K Color Temp. 35K - 3500K Color Temp. 30K - 3000K Color Temp. 27K - 2700K Color Temp. (Standard) F - Fused PCL120 - Photocell 120V PCL277 - Photocell 277V TP - Tamper Resistant Screws DIM - Dimming Ballast * (QE Electronic Only) EBW - Integral Emergency Battery** (Electronic Only) (1x13W & 1x18W Only) MSP - Program Start Ballast (Recommended for Motion Sensor) ***

**REPLACEMENT PARTS**

**PART NO.**

Frosted Glass Lens	3700862
White Polycarbonate Lens	3403960
Birdie CA GRL Fascia	5510599
Birdie CA EYE Fascia	5510199
Birdie CA RNG Fascia	5509999
Birdie CA EVG Fascia	5503599
(Please Specify Color of Fascia When Ordering)	

**NOTES**

\*QE Electronic Only

\*\*Emergency Battery Options

Initial light output in Emergency mode will last for a minimum of 90 minutes. 1 lamp wired unless ordered otherwise. The following are suitable for indoor and damp locations. Please refer to Bodine's specification sheet

EBW:

Bodine CF94GU (Electronic) - Temperature Rating (Ambient) 32° F - 131° F

We reserve the right to revise the design or components of any product due to parts availability or change in UL standards, without assuming any obligation or liability to modify any products previously manufactured, and without notice.

\*\*\* For Electronic Wattage Fixtures Being Used in Conjunction With an Occupancy Sensor (Either Provided by us, or Your Own System), a Program Start Ballast is Recommended in Order to Maximize Lamp Life.

ARRA 2009



BUY AMERICA ACT C US