





PROJECT :
TYPE :
ORDERING # :
COMMENTS :

EVEREST

FEATURES



- Steel Housing w/ White Powder Coat Finish
- Steel Internal Divider w/ Hi-Reflectance White Powder Coat Finish
- Custom Steel Shield w/ Textured White Powder Coat Finish (Shield Attaches to Bayside Housing)
- Clear Ribbed Acrylic Lens
- Up / Down Lighting
- Mounts Directly to Surface w/ Two Wall Anchors (Not Included)
- Lamps Not Included
- Convenience Outlet Available
- Dual and Multi-Switches w/ Pull Chains Available
- CSA Listed Damp Location



ORDERING INFORMATION

Example : (EVT- F48332E - 120E - TW - MSWR)

PRODUCT	SOURCE/WATTAGE	VOLTAGE	DIFFUSER	FINISH	OPTIONS
Everest (48" Fixture)	F48232E - (2) 32W T8 F48228E - (2) 28W T5 F48332E - (3) 32W T8 F48328E - (3) 28W T5 F48432E - (4) 32W T8	120E - 120V Electronic 277E - 277V Electronic 347E - 347V Electronic	Not Applicable	WH - Gloss White TB - Textured Black AC - Antique Copper AS - Antique Silver BT - Bronze Mist KC - Kenworth Chrome SN - Sand SW - Swedish Steel BZ - Textured Bronze TW - Textured White RAL Colors or Custom Match - Consult Factory	CO - Convenience Outlet F - Fused MSWR - Multi-Lamp Switch w/ Pull Chain on Right Side (For 3-Lamp Fixtures) MSWL - Multi-Lamp Switch w/ Pull Chain on Left Side (For 3-Lamp Fixtures) 2SWR - 2-Lamp Switch w/ Pull Chain on Right Side (For 2-Lamp Fixtures) 2SWL - 2-Lamp Switch w/ Pull Chain on Left Side (For 2-Lamp Fixtures) NLT - Night Light (7W or 9W) (2 & 3 Lamp Fixtures Only) EB - Integral Emergency Battery (120 & 277V Only)

REPLACEMENT PARTS	PART NO.
48" Clear Acrylic Diffuser	30049

NOTES

We reserve the right to revise the design or components of any product due to parts availability or change in UL standards, without assuming any obligation or liability to modify any products previously manufactured, and without notice.

****Emergency Battery Options**
Initial light output in Emergency mode will last for a minimum of 90 minutes. 1 lamp wired unless ordered otherwise. The following are suitable for indoor and damp locations. Please refer to Bodine's specification sheet
EB: Bodine's B50 (Electronic) - Temperature Rating (Ambient) 32° F - 131° F

