



ARCHITECTURAL INDOOR

**CONCORDE S**





COMPACT FLUORESCENT

PROJECT :
TYPE :
ORDERING # :
COMMENTS :

**FEATURES**

- Steel Perforated Fascia w/ Matte Silver Powder Coat Finish
- Matte White Acrylic Diffuser
- Steel Mounting Pan w/ Hi-Reflectance White Powder Coat Finish
- Top & Bottom Perforated Covers
- Mounts Directly to 4" Junction Box (By Others)
- Mounting Hardware Included
- Lamps Included
- Integral EM Battery Available
- ADA Compliant
- ETL Listed Dry Location
- Wattages With a (ES) Are Available @ 120V  
With Energy Star Compliant Lamps and Ballasts



**ORDERING INFORMATION**

Example : (CNCS - F226Q - 120E - WAL - SM - 41K)

Matte Silver is Standard Finish

PRODUCT	SOURCE/WATTAGE	VOLTAGE	DIFFUSER	FINISH	OPTIONS
Concorde S	F213E - (2) 13W 4-Pin Biax F218Q - (2) 18W QE F226Q - (2) 26W QE (ES)	120E - 120V Electronic 277E - 277V Electronic	WAL - White Acrylic	WH - Gloss White (Standard) SM - Matte Silver TB - Textured Black AC - Antique Copper AS - Antique Silver BT - Bronze Mist CP - Copper KC - Kenworth Chrome SN - Sand SW - Swedish Steel BZ - Textured Bronze TW - Textured White  RAL Colors or Custom Match - Consult Factory	41K - 4100K Color Temp. (Standard) 35K - 3500K Color Temp. (Except F213E) 27K - 2700K Color Temp. F - Fused DIM - Dimming Ballast (Electronic Only) EBW - Integral Emergency Battery* EBR - Remote Mount Battery (Field Installed)* W2L - Wire 2 Lamps to Integral Emergency Battery (2x18W Max) ES - Energy Star Listed Fixture w/ Compliant Ballasts & Lamps

**REPLACEMENT PARTS**

**PART NO.**

White Acrylic Lens	3015660
--------------------	---------

**NOTES**

**\*Emergency Battery Options**

Initial light output in emergency mode will last for a minimum of 90 minutes. 1 Lamp wired unless specified otherwise. The following are suitable for indoor locations. Please refer to Bodine's Specification sheet.

**EBW:**

Bodine's B94G - Temperature Rating (Ambient) 32 °F to 131° F

**EBR:**

Bodine's B94CG (Electronic) - Temperature Rating (Ambient) 32° F to 122° F

We reserve the right to revise the design or components of any product due to parts availability or change in UL standards, without assuming any obligation or liability to modify any products previously manufactured, and without notice.

ARRA 2009

