MAMBA SMALL LED

Architectural Outdoor





FEATURES

- ADA Compliant
- Black Powder Coated Steel Housing
- Clear Glass Outside With Opal White Interior
- ETL/cETL Listed Wet Location For Wall Mount

PROJECT: TYPE:

COMMENTS:

PO#:

- IP54 Certified
- LED Light Fixture
- T24 Compliant
- Vertical Or Horizontal Wall Mount
- 120V Only Triac Dimmable Driver
- 4.1 lbs.
- 90 CRI


LINE DRAWING

LINE DRAWING NOT TO SCALE

QTY:



Ø 1/2"



FINISHES

Black



For RAL Colors & Custom Match -Contact Teron Lighting Inc.



 TERONLIGHTING.COM

 33 DONALD DR, FAIRFIELD, OH 45014

 P: 513.858.6004

 F: 513.858.6038

 E: SALES@TERONLIGHT.COM

MAMBA SMALL LED

Architectural Outdoor

6. 🕕 🖻

	PROJECT:	
	TYPE:	
	PO#:	QTY:
	COMMENTS:	

Fixture Core			
PRODUCT CODE	SOURCE/WATTAGE	VOLTAGE	DIMMING DRIVER
MBSM - Mamba Small LED	L16.0-LTXXX - 16.0W @ XXXmA Constant Current Electronic Driver Note: Driver Current Information Coming Soon	120V	LT - TRIAC Dimming
MBSM	L16.0-LTXXX	120V	Not Applicable

Aesthetics & Options

TRIM		FINISH	COLOR TEMP		OPTIONS	
Not Applicabl	le	BLK - Black	30K - 3000K Col	or Temp	Not Applicable	
RDER INFO						
Not Applica	ble	BLK	30K		Not Applicable	
Example ^						
PROD	SOURCE	30K SPECS				
MBSM	L16.0	 30K - 3000K Color Temp 850 LED Source Lumens 53.1 LED Source Lumens Per Watt 413 Delivered Lumens 25.8 Delivered Lumens Per Watt 				
REPLAC	EMENT PART	PART NO NOTE	S	1	I	
				Don't se	e the configuration you are looki	ing for?



TERONLIGHTING.COM 33 DONALD DR, FAIRFIELD, OH 45014 P: 513.858.6004 F: 513.858.6038 E: SALES@TERONLIGHT.COM

We reserve the right to revise the design components of any product due to parts availability or change in UL standards, without assuming any obligation or liability to modify any products previously manufactured, and without notice. 2

Call us today at (513) 858-6004