MAMBA SQUARE LED

Architectural Outdoor

Æ.	(Th)	h	F	3	

PF	OJECT:	
TY	PE:	
PC)#:	QTY:
CC	DMMENTS:	






FEATURES

- ADA Compliant
- Black Powder Coated Steel Housing
- Clear Glass Outside With Opal White Interior
- Ceiling or Wall Mounted
- ETL/cETL Listed Wet Location For Ceiling Mount
- IP54 Certified
- LED Light Fixture
- T24 Compliant
- 120V Only Triac Dimmable Driver
- 7.3 lbs.
- 90 CRI



LINE DRAWING

LINE DRAWING NOT TO SCAL





FINISHES

Black



For RAL Colors & Custom Match -Contact Teron Lighting Inc.



MAMBA SQUARE LED

Architectural Outdoor

볏. ⑩ 년	6	(11)	LED
---------------	---	------	-----

CH	itec	tur	al	υu	ιu	OOI

Fixture Core

PROJECT:	
TYPE:	
PO#:	QTY:
COMMENTS:	

PRODUCT CODE	SOURCE/WATTAGE	VOLTAGE	DIMMING DRIVER
MBSQ - Mamba Square LED	L25.0-LTXXX - 25.0W @ XXXmA Constant Current Electronic Driver Note: Driver Current	120V	LT - TRIAC Dimming
ORDER INFO	Information Coming Soon		
MBSQ	L25.0-LTXXX	120V	LT

Aesthetics & Options

TRIM	FINISH	COLOR TEMP	OPTIONS
Not Applicable	BLK - Black	30K - 3000K Color Temp	Not Applicable
ORDER INFO Not Applicable	BLK	30K	Not Applicable

MBSQ L25.0 • 30K - 3000K Color Temp	PROD	SOURCE	30K SPECS		
Source Lumens 48.0 LED Source Lumens Per Watt 893 Delivered Lumens 35.7 Delivered Lumens Per Watt			30K - 3000K Color Temp 1200 LED Source Lumens 48.0 LED Source Lumens Per Watt 893 Delivered Lumens 35.7 Delivered		

REPLACEMENT PART	PART NO	NOTES
		Don't see the configuration you are looking for?
		Call us today at (513) 858-6004

