

# PARISIAN DOUBLE LED

Architectural Indoor




PROJECT:	
TYPE:	
PO#:	QTY:
COMMENTS:	

## FEATURES

- Adjustable Wire Cable
- Ceiling Mounted
- Dimmable @ 120V
- ETL/cETL Listed for Dry Locations
- LED Light Fixture
- Steel Composition
- 10 lbs.
- 2 Total Lights
- 80+ CRI

## LINE DRAWING

LINE DRAWING NOT TO SCALE



## FINISHES

Chrome



For RAL Colors  
& Custom  
Match -  
**Contact Teron  
Lighting Inc.**

# PARISIAN DOUBLE LED

Architectural Indoor



Fixture Core

PROJECT:

TYPE:

PO#:

QTY:

COMMENTS:

PRODUCT CODE	SOURCE/WATTAGE	VOLTAGE	DIMMING DRIVER
PSND - Parisian Double LED	L52.0-LTXXX - 52.0W @ XXXmA ELV Low Voltage 2-Wire Dimming Electronic Driver (Leading or Trailing Edge)  Note: Driver Current Information Coming Soon	120V	TRIAC Dimming @ 120V
ORDER INFO			
PSND Example ^	L52.0-LTXXX	120V	TRIAC

Aesthetics & Options

TRIM	FINISH	COLOR TEMP	OPTIONS
Not Applicable	CM - Chrome	30K - 3000 Color Temp	Not Applicable
ORDER INFO			
Not Applicable Example ^	CM	30K	Not Applicable

PROD	SOURCE	30K SPECS				
PSND	L52.0	<ul style="list-style-type: none"><li>30K - 3000K Color Temp</li><li>3900 LED Source Lumens</li><li>37.5 LED Source Lumens Per Watt</li></ul>				

REPLACEMENT PART	PART NO	NOTES
		Don't see the configuration you are looking for? Call us today at (513) 858-6004



TERONLIGHTING.COM  
33 DONALD DR, FAIRFIELD, OH 45014  
P: 513.858.6004 F: 513.858.6038  
E: SALES@TERONLIGHT.COM

We reserve the right to revise the design components of any product due to parts availability or change in UL standards, without assuming any obligation or liability to modify any products previously manufactured, and without notice.