



BRONZE CUP MD LED



PROJECT :
TYPE :
ORDERING # :
COMMENTS :

FEATURES

- Cast Aluminum Housing w/ Textured Bronze Polyester Powder Coat Finish
- Clear Prismatic Borosilicate Glass Lens
- Permlight BB66WA 35W LED Module
- Antron AC-50CDI.4UV-TS 50W LED Driver
- Surge Protector
- Fully Gasketed
- Stainless Steel Zinc-Coated Screws
- Mounts Direct to Flat Surface w/ Four #8 Wall Anchors (Not Included)
- Cast-In Template
- Ideal For Stairwell And Passageway Lighting
- CSA Listed For Wall Mounting
- L70 Life Time For 50,000hr



0.50" Conduit Entries
One Each on Opposite Sides, One On Top, and One on Back of Housing

ORDERING INFORMATION

Example : (BPM - L35.0 - 100 - 277V - CGL - TB - 50K)

Textured Bronze is Standard Finish

PRODUCT	SOURCE/WATTAGE	VOLTAGE	DIFFUSER	FINISH	OPTIONS
Bronze Cup Md	L35.0 - 35W LED Module	100 - 277V	CGL - Clear Glass Lens (Standard)	SM - Matte Silver TB - Textured Black AC - Antique Copper AS - Antique Silver BT - Bronze Mist CP - Copper SN - Sand SW - Swedish Steel BZ - Textured Bronze TW - Textured White RAL Colors or Custom Match - Consult Factory	40K - 4000K Color Temperature 50K - 5000K Color Temperature PCL120 - Photocell 120V PCL277 - Photocell 277V DIM - Dimmable Driver (0 - 10V) SDIM - Step-Dimmable Driver (Dimmable to 25% & 50%) PDIM - Pulse Width Dimmable Driver (0 - 10V) F - Fused EB - Bodine BSL23 - Will light Two 5.5W LED Strips - Average 340 total Lumens Please Note: 120V or 277V Must Be Specified When Ordering The EB Option Driver Specifications - 66 LEDs Per Strip - SW50Bin, Color Temp = 5000K Nominal - Constant Current at 1050mA by Driver - 80 CRI typ. (75 CRI min) 4200 Lumens - 41W Input = Estimated 102 Lumens Per Watt

REPLACEMENT PARTS	PART NO.
Clear Tempered Glass Diffuser	37033
Dark Sky Visor (Please Specify Color When Ordering) (Must Order Separately)	5301999

NOTES

We reserve the right to revise the design or components of any product due to parts availability or change in UL standards, without assuming any obligation or liability to modify any products previously manufactured, and without notice.





PROJECT :
TYPE :
ORDERING # :
COMMENTS :

PRODUCT	SOURCE/WATTAGE	40K SPECIFICATIONS	50K SPECIFICATIONS
Bronze Cup MD LED	L35.0 - (1) 35W LED Board	LED Specifications - 66 LEDs Per Strip - SW50Bin, Color Temp = 4000K Nominal - Constant Current at 1050mA by Driver - 80 CRI typ. (75 CRI min) 3990 Lumens - 41W Input = Estimated 97 Lumens Per Watt	LED Specifications - 66 LEDs Per Strip - SW50Bin, Color Temp = 5000K Nominal - Constant Current at 1050mA by Driver - 80 CRI typ. (75 CRI min) 4200 Lumens - 41W Input = Estimated 102 Lumens Per Watt

ARRA 2009



BUY AMERICA ACT C US