INSTALLATION & MAINTENANCE INSTRUCTIONS

DRIVER

Outdoor Wall Lighting



INSTALLATION

NOTE: THIS PRODUCT MUST BE INSTALLED IN ACCORDANCE WITH THE APPLICABLE INSTALLATION CODE BY A PERSON FAMILIAR WITH THE CONSTRUCTION AND OPERATION OF THE PRODUCT AND THE HAZARDS INVOLVED.

- 1] Remove any excess packing from the fixture.
- 2] Remove the door from the housing and set aside.
- 3] The Driver Series is designed to be mounted directly to the wall by using 2 to 4 anchor bolts, with the installer selecting, and drilling, the holes out that they wish to use for installation.
- NOTE: Do NOT use the center hole for mounting. It is intended to be used as a wireway ONLY.
- 5] Connect the fixture leads to the supply leads. TLI stipulates the Black as Line; White as Common; Bare/Green as Ground.
- 6] Check the re-lamp label to ensure that the lamp is the specified wattage. HID Lamps should be hand tight. For best operation, screw in the HID lamp, remove, & re-tighten.
- 7] Re-attach the door to the housing and secure the screws.
- 8] Outdoor wall fixtures must be caulked with a suitable waterproof sealant across the top, and at least 2" down each side of the fixture to properly seal it to the mounting surface. A small space should be open at the bottom for excess moisture runoff.

MAINTENANCE

The lens should be cleaned once every 6 months. Repeat the above procedures in reverse to remove the lens. It must be washed in a mild soap solution. DO NOT use cleansers containing bleach. Re-assemble the fixture.

The metal portion of the fixture can be wiped clean as needed using a mild soap solution.

ATTENTION: Avoid moving any exposed wires. If any wires are accidentally disconnected, call a professional to repair.

These instuctions are general to the fixtures noted. Due to the numerous options, all variations may not be covered.



Installation of an electrical luminaire must be performed by a qualified professional. The fixture must be wired in accordance to all local & national electrical codes.