## INSTALLATION & MAINTENANCE INSTRUCTIONS VANITY SERIES

## TURNBERRY GUARDIAN W



Echelon

**SCREWS** 

(BY OTHERS)



76059

NOTE: THIS PRODUCT MUST BE INSTALLED IN ACCORDANCE WITH THE APPLICABLE INSTALLATION CODE BY A PERSON FAMILIAR WITH THE CONSTRUCTION AND OPERATION OF THE PRODUCT AND THE HAZARDS INVOLVED.

## INSTALLATION

- 1] Remove any excess packing from the fixture.
- 2] Vanity housing are designed to be mounted directly to the wall with (2) anchors. There are (2) mount holes in housing. Measure the distance between the holes, & mark the surface for each housing to be installed.
- 3] Pull the supply leads into the housing, and mount the housing to the wall with anchors.
- 4] Connect the fixture leads to the supply leads. Teron stipulates the Black as Line, White as Common, and Bare/Green as ground.
- 5] The lenses can be removed and reinstalled as follows:

Remove one end cap. Slide the lens a few inches towards the end that was removed, then pull the lens directly out of the tracks. This can be done due to the DR / Acrylic blend of the lens material, which allows it to be durable, yet flexible. To re-install the lens, slide one edge of the lens into the track on one side of the housing, then push the other edge into the remaining track to snap the lens back into place. Reattach the end cap that was removed.

- 6] Check the re-lamp label to ensure that the lamp is the specified wattage. Energize the fixture to check proper operation.
- 7] Outdoor wall fixtures must be caulked with a suitable waterproof sealant across the top, and at least 2" down each side of the fixture to properly seal it to the mounting surface. A small space should be open at the bottom for excess moisture runoff.

## **MAINTENANCE**

The lens should be cleaned once every 6 months. Repeat the above procedures in reverse to remove the lens. It must be washed in a mild soap solution. DO NOT use cleaners containing bleach.

Re-assemble the fixture.

The metal portion of the fixture can be wiped clean as needed using a mild soap solution.

ATTENTION: Avoid moving any exposed wires. If any wires are accidentally disconnected, call a professional to repair.

These instuctions are general to the fixtures noted. Due to the numerous options, all variations may not be covered. Installation of an electrical luminaire must be performed by a qualified professional. The fixture must be wired in accordance to all local & national electrical codes.