

PROJECT :
TYPE :
ORDERING # :
COMMENTS :

CITADEL X




Textured White Finish Shown

COMPACT FLUORESCENT & HID

FEATURES

- Steel Housing w/ Textured Black Polyester Powder Coat Finish
- Frosted Tempered Glass Lens Panels - 4 Sides
- Steel Fascia w/ Textured Black Polyester Powder Coat Finish
- Smooth Anod Aluminum Reflector
- Mounts Directly to 4" Junction Box (By Others) J-Box Centered in Fixture
- Mounting Hardware Included
- Lamps Included
- Electronic Wattages Are CSA Listed For Wall Mount



ORDERING INFORMATION

Example : (CTDX - F226Q - 120E - TB - 41K) Textured Black is Standard Finish

PRODUCT	SOURCE/WATTAGE	VOLTAGE	DIFFUSER	FINISH	OPTIONS
Citadel X	M50 - 50W MH M70 - 70W MH S50 - 50W HPS S70 - 70W HPS S100 - 100W HPS F218Q - (2) 18W QE F226Q - (2) 26W QE F232X - (2) 32W TBX F142X - (1) 42W TBX	<u>HID (HPS & MH)</u> DTH - Dual-Tap HPF** <u>FLUORESCENT</u> 120E - Electronic 120V 277E - Electronic 277V 347E - Electronic 347V	Not Applicable	SM - Matte Silver TB - Textured Black AC - Antique Copper AS - Antique Silver BT - Bronze Mist CP - Copper SN - Sand SW - Swedish Steel BZ - Textured Bronze TW - Textured White RAL Colors or Custom Match - Consult Factory	41K - 4100K Color Temp. (Standard) 35K - 3500K Color Temp. 30K - 3000K Color Temp. 27K - 2700K Color Temp. DIM - Dimming Ballast (Electronic Only) F - Fused (Not Available For 347V) EBR - Remote Mount Battery (Field Installed)* SCV - Steel Slide Covers (To Allow Up/Down Lighting) MSP - Program Start Ballast (Recommended for Motion Sensor) ***

REPLACEMENT PARTS PART NO.

Glass Lens Panel Set	98005
Fascia (Specify Fascia Color)	5595299

We reserve the right to revise the design or components of any product due to parts availability or change in UL standards, without assuming any obligation or liability to modify any products previously manufactured, and without notice.

NOTES

***Emergency Battery Options**
Initial light output in Emergency mode will last for a minimum of 90 minutes. 1 lamp wired unless ordered otherwise. The following are suitable for indoor and damp locations. Please refer to Bodine's specification sheet
EBR:
Bodine's B94CG (Electronic) - Temperature Rating (Ambient) 32° F - 122° F
****Remote Mount Ballast:**
Max Mounting Distance: MH - 20 Ft., HPS - 10 Ft.
To insure proper operation, remote HID ballasts must be vented and mounted to a heat dissipating surface.

*** For Electronic Wattage Fixtures Being Used in Conjunction With an Occupancy Sensor (Either Provided by us, or Your Own System), a Program Start Ballast is Recommended in Order to Maximize Lamp Life.

