Architectural Outdoor







FEATURES

- · Clear Tempered Glass Diffusers
- Constant Voltage Modules (Excluding L218.1)

PROJECT: TYPE: PO#:


COMMENTS:

- CSA Listed Wet Location
- Die-Cast Aluminum Housing w/ Textured Black Polyester Powder Coat Finish
- Emergency Battery Available
- · LED Light Fixture
- Mounts Direct to Flat Surface w/ Two #8 Wall Anchors (Not Included)
- Surge Protector
- Thermal Compensation Technology Ensures Longer LED Lifetime Ideal For Fixtures Being Placed in Area w/ Fluctuating or Higher Ambient Temperatures (Excluding L218.1)

LINE DRAWING

INF DRAWING NOT TO SCALE

QTY:



FINISHES Antique Antique Bronze Matte Sand Swedish Copper Silver Steel Mist Silver Textured Textured Textured Black Bronze White For RAL Colors & Custom Match -**Contact Teron** Lighting Inc.





Architectural Outdoor







Fixture Core

ı	PROJECT:	
	TYPE:	
	PO#:	QTY:
	COMMENTS:	

PRODUCT CODE	SOURCE/WATTAGE	VOLTAGE	DIMMING DRIVER
CRNW - Cornerstone W	L112.3-12CV - 16W @ 12V Constant Voltage Non-Dimming Driver (UL/DL required) L212.3-12CV - 32W @ 12V Constant Voltage Non-Dimming Driver		Not Applicable
ORDER INFO	511101		
	144004004	400 0771	
CRNW	L112.3-12CV	120 - 277V	Not Applicable

Example ^ (may not represent a manufacturable product)

Aesthetics & Options

TRIM	FINISH	COLOR TEMP	OPTIONS
Not Applicable	AC - Antique Copper AS - Antique Silver BT - Bronze Mist SM - Matte Silver SN - Sand SW - Swedish Steel TB - Textured Black (Standard) BZ - Textured Bronze TW - Textured White	30K - 3000K Color Temp 35K - 3500K Color Temp 40K - 4000K Color Temp 50K - 5000K Color Temp	DL - Downlight Only EB - Integral EM Battery (Downlight) (L112.3 Only) F - Fused PCL - Photocell TP - Tamper Resistant UL - Uplight Only (L112.3 Only)
ORDER INFO			
Not Applicable	AC	30K	DL

Example ^ (may not represent a manufacturable product)

PROD	SOURCE	30K SPECS
CRNW	L112.3	30K - 3000K Color Temp 1264 LED Source Lumens 102.8 LED Source Lumens Per Watt 1285 Delivered LED Lumens 71.4 Delivered LED Lumens Per Watt
	L212.3	 30K - 3000K Color Temp 2528 LED Source Lumens 78 LED Source Lumens Per Watt 2355 Delivered LED Lumens 70.4 Delivered Lumens Per Watt

REPLACEMENT PART	PART NO	NOTES
Black Glass Lens	3702824	
Clear Glass Lens	37028	Don't see the configuration you are looking for? Call us today at (513) 858-6004



E: SALES@TERONLIGHT.COM

Architectural Outdoor







		•				
ixture Core						
PRODUCT CODE	SOURCE/WATTAGE	VOLTAGE	DIMMING DRIVER			
CRNW - Cornerstone W	L124.5-12CV - 32W @ 12V Constant Voltage Non-Dimming Driver (UL/DL required)	120 - 277V	Not Applicable			
ORDER INFO	L224.5-12CV - 64W @ 12V Constant Voltage Non-Dimming Driver					

PROJECT: TYPE:

COMMENTS:

QTY:

PO#:

Aesthetics & Options

TRIM	FINISH	COLOR TEMP	OPTIONS
Not Applicable ORDER INFO	AC - Antique Copper AS - Antique Silver BT - Bronze Mist SM - Matte Silver SN - Sand SW - Swedish Steel TB - Textured Black (Standard) BZ - Textured Bronze TW - Textured White	30K - 3000K Color Temp 35K - 3500K Color Temp 40K - 4000K Color Temp 50K - 5000K Color Temp	DL - Downlight Only EB - Integral EM Battery (Downlight) (L112.3 Only) F - Fused PCL - Photocell TP - Tamper Resistant UL - Uplight Only (L112.3 Only
Not Applicable	AC	30K	DL

Example ^ (may not represent a manufacturable product)

PROD	SOURCE	30K SPECS
CRNW	L124.5	• 30K - 3000K Color Temp • 2528 LED Source Lumens • 103.2 LED Source Lumens Per Watt • 2442 Delivered LED Source Lumens • 76.3 Delivered Lumens Per Watt
	L224.5	• 30K - 3000K Color Temp • 5056 LED Source Lumens • 102.1 LED Source Lumens Per Watt • 4796 Delivered LED Lumens • 74.9 Delivered LED Lumens Per Watt

REPLACEMENT PART	PART NO	NOTES
Black Glass Lens	3702824	
Clear Glass Lens	37028	Don't see the configuration you are looking for? Call us today at (513) 858-6004



Example ^ (may not represent a manufacturable product)

Architectural Outdoor









Fixture Core

_	
PROJECT:	
TYPE:	
PO#:	QTY:
COMMENTS:	

PRODUCT CODE	SOURCE/WATTAGE	VOLTAGE	DIMMING DRIVER
CRNW - Cornerstone W	L115.3-ZE12V - 20W @ 0-10V Dimming Driver Downlight L221.5-ZE12V - 56W @ 0-10V Dimming Drive	120 - 277V	Not Applicable
ORDER INFO			
CRNW	L115.3-ZE12V	120 - 277V	Not Applicable

Aesthetics & Options

TRIM	FINISH	COLOR TEMP	OPTIONS
Not Applicable	AC - Antique Copper AS - Antique Silver BT - Bronze Mist SM - Matte Silver SN - Sand SW - Swedish Steel TB - Textured Black (Standard) BZ - Textured Bronze TW - Textured White	30K - 3000K Color Temp 35K - 3500K Color Temp 40K - 4000K Color Temp 50K - 5000K Color Temp	DL - Downlight Only EB - Integral EM Battery (Downlight) (L112.3 Only) F - Fused PCL - Photocell TP - Tamper Resistant UL - Uplight Only (L112.3 Only)
ORDER INFO			
Not Applicable	AC	30K	DL

Example ^ (may not represent a manufacturable product)

PROD	SOURCE	BOK SPECS
CRNW	L115.3	• 30K - 3000K Color Temp • 1580 LED Source Lumens • 103.3 LED Source Lumens Per Watt • 1541 Delivered LED Lumens • 73.4 Delivered LED Lumens
	L221.5	• 30K - 3000K Color Temp • 4424 LED Source Lumens • 102.9 LED Source Lumens Per Watt • 4057 Delivered LED Lumens • 72.4 Delivered LED Lumens Per Watt

REPLACEMENT PART	PART NO	NOTES
Black Glass Lens	3702824	
Clear Glass Lens	37028	Don't see the configuration you are looking for? Call us today at (513) 858-6004



E: SALES@TERONLIGHT.COM

Architectural Outdoor







Fixture Core

PROJECT:	
TYPE:	
PO#:	QTY:
COMMENTS:	

PRODUCT CODE	SOURCE/WATTAGE	VOLTAGE	DIMMING DRIVER
CRNW - Cornerstone W	L218.1-ZE1100 - 42W @ 1100mA 0-10V Dimming Driver	120 - 277V	Not Applicable
ORDER INFO			
ORDER INFO			

Aesthetics & Options

TRIM	FINISH	COLOR TEMP	OPTIONS
Not Applicable ORDER INFO	AC - Antique Copper AS - Antique Silver BT - Bronze Mist SM - Matte Silver SN - Sand SW - Swedish Steel TB - Textured Black (Standard) BZ - Textured Bronze TW - Textured White	30K - 3000K Color Temp 35K - 3500K Color Temp 40K - 4000K Color Temp 50K - 5000K Color Temp	DL - Downlight Only EB - Integral EM Battery (Downlight) (L112.3 Only) F - Fused PCL - Photocell TP - Tamper Resistant UL - Uplight Only (L112.3 Only)
51.5 <u>2.</u> 11.11.0			
Not Applicable	I AC	30K	DL

Example ^ (may not represent a manufacturable product)

CRNW L218.1 • 30K - 3000K Color Temp • 5465 LED Source Lumens • 151 LED Source Lumens Per Watt • 4132 Delivered LED Lumens • 98.4 Delivered LED Lumens per Watt	PROD	SOURCE	30K SPECS		
	CRNW	L218.1	Color Temp • 5465 LED Source Lumens • 151 LED Source Lumens Per Watt • 4132 Delivered LED Lumens • 98.4 Delivered LED		

REPLACEMENT PART	PART NO	NOTES
Black Glass Lens	3702824	
Clear Glass Lens	37028	Don't see the configuration you are looking for? Call us today at (513) 858-6004

