

NIKE C LED 14"

Architectural Indoor



PROJECT:

TYPE:

PO#:

QTY:


COMMENTS:

FEATURES

- ADA Compliant
- CSA Listed Damp Location for Ceiling and Wall Mount
- Die-Form Cold-Rolled Steel Housing w/ Brushed Nickel Plated Finish
- Emergency Battery Available
- IES Files Are Available
- LED Light Fixture
- Luminous White Acrylic Diffuser
- Mounting Hardware Included
- Mounts Directly to 4" Junction Box (By Others)
- Steel Mounting Pan w/ Hi-Reflectance White Powder Coat Finish
- Steel Trim w/ Brushed Nickel Plated Finish

LINE DRAWING

LINE DRAWING NOT TO SCALE



FINISHES

Antique Copper




Antique Silver




Bronze Mist




Matte Silver




Sand




Swedish Steel




Textured Black



Textured Bronze



Textured White



For RAL Colors
& Custom
Match -
Contact Teron
Lighting Inc.

NIKE C LED 14"

Architectural Indoor



Fixture Core

PROJECT:	
TYPE:	
PO#:	QTY:
COMMENTS:	

PRODUCT CODE	SOURCE/WATTAGE	VOLTAGE	DIMMING DRIVER
NEC14 - Nike C 14"	L13.0-ZE560 - (48) LED Array @ 560mA Line Voltage 4-Wire Dimming Driver (Dimmable 0 - 10V) L17.0-ZE530 - (60) LED Array @ 560mA Line Voltage 4-Wire Dimming Driver (Dimmable 0 - 10V)	120V 277V (50 / 60Hz)	Not Applicable
ORDER INFO			
NEC14 Example ^	L13.0-ZE560	120V	Not Applicable

Aesthetics & Options

TRIM	FINISH	COLOR TEMP	OPTIONS
Not Applicable	AC - Antique Copper AS - Antique Silver BT - Bronze Mist BN - Brushed Nickel (Standard) SM - Matte Silver SN - Sand SW - Swedish Steel TB - Textured Black BZ - Textured Bronze TW - Textured White	30K - 3000K Color Temp 35K - 3500K Color Temp 40K - 4000K Color Temp 50K - 5000K Color Temp	BB - Back Box EBW/BB - Bodine BSL26 - Up to 5.1W Emergency Illumination With LEDs (Back Box Required)* F - Fused STC12-WH - 12" Stem / Canopy Kits STC24-WH - 24" Stem / Canopy Kits STC36-WH - 36" Stem / Canopy Kits STC48-WH - 48" Stem / Canopy Kits
ORDER INFO			
Not Applicable Example ^	AC	30K	BB

PROD	SOURCE	30K SPECS				
NEC14	L13.0	<ul style="list-style-type: none">30K - 3000K Color Temp1700 LED Source Lumens105 LED Source Lumens Per Watt986 Delivered LED Lumens65.5 Delivered LED Lumens Per Watt				
	L17.0	<ul style="list-style-type: none">80 CRI Typ.30K - 3000K Color Temp2650 LED Source Lumens157 LED Source Lumens Per Watt1530 Delivered LED Lumens82.3 Delivered LED Lumens Per Watt				

REPLACEMENT PART	PART NO	NOTES
14" White Acrylic Diffuser	3049660	(All Stem Canopy Kits Are White Finish Unless Other Finish is Specified When Ordering) *Emergency Battery Options - AC Mode 960 Lumens Battery @ 1 second = 322 Total Lumens Battery @ 90 Minutes = 291 Total Lumens Don't see the configuration you are looking for? Call us today at (513) 858-6004



TERONLIGHTING.COM
33 DONALD DR, FAIRFIELD, OH 45014
P: 513.858.6004 F: 513.858.6038
E: SALES@TERONLIGHT.COM



We reserve the right to revise the design components of any product due to parts availability or change in UL standards, without assuming any obligation or liability to modify any products previously manufactured, and without notice.

NIKE C LED 14"

Architectural Indoor



Fixture Core

PROJECT:	
TYPE:	
PO#:	QTY:
COMMENTS:	

PRODUCT CODE	SOURCE/WATTAGE	VOLTAGE	DIMMING DRIVER
NEC14 - Nike C 14"	L20.5-ZE640 - (60) LED Array @ 700mA Line Voltage 4-Wire Dimming Driver (Dimmable 0 - 10V)	120V 277V (50 / 60Hz)	Not Applicable
ORDER INFO			
NEC14 Example ^	L20.5-ZE640	120V	Not Applicable

Aesthetics & Options

TRIM	FINISH	COLOR TEMP	OPTIONS
Not Applicable	AC - Antique Copper AS - Antique Silver BT - Bronze Mist BN - Brushed Nickel (Standard) SM - Matte Silver SN - Sand SW - Swedish Steel TB - Textured Black BZ - Textured Bronze TW - Textured White	30K - 3000K Color Temp 35K - 3500K Color Temp 40K - 4000K Color Temp 50K - 5000K Color Temp	BB - Back Box EBW/BB - Bodine BSL26 - Up to 5.1W Emergency Illumination With LEDs (Back Box Required)* F - Fused STC12-WH - 12" Stem / Canopy Kits STC24-WH - 24" Stem / Canopy Kits STC36-WH - 36" Stem / Canopy Kits STC48-WH - 48" Stem / Canopy Kits
ORDER INFO			
Not Applicable Example ^	AC	30K	BB

PROD	SOURCE	30K SPECS				
NEC14	L20.5	<ul style="list-style-type: none">• 80 CRI Typ.• 30K - 3000K Color Temp• 3100 LED Source Lumens• 151 LED Source Lumens Per Watt• 1861 Delivered LED Lumens• 77.4 Delivered LED Lumens Per Watt				

REPLACEMENT PART	PART NO	NOTES
14" White Acrylic Diffuser	3049660	(All Stem Canopy Kits Are White Finish Unless Other Finish is Specified When Ordering) *Emergency Battery Options - AC Mode 960 Lumens Battery @ 1 second = 322 Total Lumens Battery @ 90 Minutes = 291 Total Lumens Don't see the configuration you are looking for? Call us today at (513) 858-6004



TERONLIGHTING.COM
33 DONALD DR, FAIRFIELD, OH 45014
P: 513.858.6004 F: 513.858.6038
E: SALES@TERONLIGHT.COM



We reserve the right to revise the design components of any product due to parts availability or change in UL standards, without assuming any obligation or liability to modify any products previously manufactured, and without notice.