

# NICKLAUS LED 37"

Architectural Indoor



PROJECT:	
TYPE:	
PO#:	QTY:
COMMENTS:	




## FEATURES

- Steel Housing w/ White Powder Coat Finish
- Aluminum Reflector w/ Hi-Reflectance White Powder Coat Finish
- Luminous White Acrylic Diffuser w/ Black Marble Acrylic End Caps
- ELV Driver - Over-Voltage, Over-Current, and Short-Circuit Protection w/ Auto Recovery
- Constant Current
- Dimmable to 10% From 120V to 230V
- Mounts Directly to Surface w/ Two Wall Anchors (Not Included)
- L70 life time for 50,000hr
- ADA Compliant
- CSA Listed Damp Location For Surface Mount
- LED Light Fixture

## LINE DRAWING

LINE DRAWING NOT TO SCALE



## FINISHES

For RAL Colors  
& Custom  
Match -  
Contact Teron  
Lighting Inc.

# NICKLAUS LED 37"

Architectural Indoor



Fixture Core

PROJECT:	
TYPE:	
PO#:	QTY:
COMMENTS:	

PRODUCT CODE	SOURCE/WATTAGE	VOLTAGE	DIMMING DRIVER
NS36 - Nicklaus 37 1/2"	<b>L23.2-TE700</b> - 23.2W LED Strip(s) @ 700mA ELV Dimming Driver  <b>L23.2-ZE700</b> - 23.2W LED Strip(s) @ 700mA Line Voltage 4-Wire Dimming Driver (Dimmable 0 - 10V)	<b>120 - 277V</b>	<b>Not Applicable</b>
ORDER INFO			
NS36 Example ^	L23.2-TE700	120 - 277V	Not Applicable

Aesthetics & Options

TRIM	FINISH	COLOR TEMP	OPTIONS
<b>Not Applicable</b>	<b>Optional End Cap Colors Available</b> - Consult Factory For Details and Pricing	<b>30K</b> - 3000K Color Temp <b>35K</b> - 3500K Color Temp <b>40K</b> - 4000K Color Temp	<b>F</b> - Fused
ORDER INFO			
Not Applicable Example ^		30K	F

PROD	SOURCE	30K SPECS			
NS36	L23.2	<ul style="list-style-type: none"> <li>30K - 3000K Color Temp</li> <li>3258 LED Source Lumens</li> <li>114.7 LED Source Lumens Per Watt</li> </ul>			

REPLACEMENT PART	PART NO	NOTES
36" White Acrylic w/ Black Marble LED Lens Assembly	3822051	Don't see the configuration you are looking for? Call us today at (513) 858-6004



**TERONLIGHTING.COM**  
 33 DONALD DR, FAIRFIELD, OH 45014  
 P: 513.858.6004 F: 513.858.6038  
 E: SALES@TERONLIGHT.COM



We reserve the right to revise the design components of any product due to parts availability or change in UL standards, without assuming any obligation or liability to modify any products previously manufactured, and without notice.

# NICKLAUS LED 37"

Architectural Indoor



Fixture Core

PROJECT:	
TYPE:	
PO#:	QTY:
COMMENTS:	

PRODUCT CODE	SOURCE/WATTAGE	VOLTAGE	DIMMING DRIVER
NS36 - Nicklaus 37 1/2"	L30.0-TE875 - 30.0W LED Strip(s) @ 875mA ELV Dimming Driver  L30.0-ZE875 - 30.0W LED Strip(s) @ 875mA Line Voltage 4-Wire Dimming Driver (Dimmable 0 - 10V)	120 - 277V	Not Applicable
ORDER INFO			
NS36 Example ^	L30.0-TE875	120 - 277V	Not Applicable

Aesthetics & Options

TRIM	FINISH	COLOR TEMP	OPTIONS
Not Applicable	Optional End Cap Colors Available - Consult Factory For Details and Pricing	30K - 3000K Color Temp 35K - 3500K Color Temp 40K - 4000K Color Temp	F - Fused
ORDER INFO			
Not Applicable Example ^		30K	F

PROD	SOURCE	30K SPECS			
NS36	L30.0	<ul style="list-style-type: none"> <li>30K - 3000K Color Temp</li> <li>4072 LED Source Lumens</li> <li>114.7 LED Source Lumens Per Watt</li> </ul>			

REPLACEMENT PART	PART NO	NOTES
36" White Acrylic w/ Black Marble LED Lens Assembly	3822051	Don't see the configuration you are looking for? Call us today at (513) 858-6004



TERONLIGHTING.COM  
33 DONALD DR, FAIRFIELD, OH 45014  
P: 513.858.6004 F: 513.858.6038  
E: SALES@TERONLIGHT.COM



We reserve the right to revise the design components of any product due to parts availability or change in UL standards, without assuming any obligation or liability to modify any products previously manufactured, and without notice.