### CAPRI LED 36"

Architectural Indoor

# £ \$ =



#### PROJECT: TYPE: COMMENTS:

QTY:

### **FEATURES**

- ADA Compliant
- CSA Listed Damp Location For Wall or Ceiling Mounting

PO#:

- L38.0 is Dimmable at 120V Only
- LED Light Fixture
- Luminous White Acrylic Diffuser
- Mounts Directly to Surface w/ Two Wall Anchors (Not Included)
- Steel Housing w/ Matte Silver Powder Coat Finish
- Steel Mounting Pan w/ Hi-Reflectance White Powder Coat Finish
- Steel Reflector w/ Hi-Reflectance White Powder Coat Finish

	LINE DRA	WING —			LINE DF	AWING NOT TO SCALE
					3 7/8" -	
			24 7/8 36 7/8 48 7/8			
C					5 3/4"	
	FINISHES					
	Antique Copper	Antique Silver	Bronze Mist	Matte Silver	Sand	Swedish Steel
	Textured Black	Textured Bronze	Textured White			
						For RAL Colors & Custom Match - <b>Contact Teron</b> Lighting Inc.



TERONLIGHTING.COM 33 DONALD DR, FAIRFIELD, OH 45014 P: 513.858.6004 F: 513.858.6038 E: SALES@TERONLIGHT.COM



We reserve the right to revise the design components of any product due to parts availability or change in UL standards, without assuming any obligation or liability to modify any products previously manufactured, and without notice.

## CAPRI LED 36"

Architectural Indoor

£ 🕀 📼

### PROJECT: QTY: COMMENTS:

Fixture Core PRODUCT CODE CPR36 - Capri 36"	SOURCE/WATTAGE L35.0-ZE1100 - 35W @ 1100mA 0-10V Dimming Driver L38.0-LT1200 - 38W @1200mA ELV Dimming Driver (Dimmable at 120V Only)	VOLTAGE 120V 277V	DIMMING DRIVER Not Applicable	
ORDER INFO				
CPR36	L35.0-ZE1100	120V	Not Applicable	

TYPE:

PO#:

#### Aesthetics & Options

Not			
Applicable	AS - Antique Silver BT - Bronze Mist B SM - Matte Silver (Standard) T	B - Textured       30K - 3000K Color Temp         Black       35K - 3500K Color Temp         AZ - Textured       40K - 4000K Color Temp         W - Textured       50K - 5000K Color Temp         White       50K - 5000K Color Temp	F - Fused TP - Tamper Resistant Screws
Not Applicable	AC	27К	

PROD	SOURCE	30K SPECS		
CPR 36"	L35.0	<ul> <li>30K - 3000K Color Temp</li> <li>5073 LED Source Lumens</li> <li>145 LED Source Lumens Per Watt</li> </ul>		
	L38.0	<ul> <li>30K - 3000K Color Temp</li> <li>5508 LED Source Lumens</li> <li>145 LED Source Lumens Per Watt</li> </ul>		

REPLACEMENT PART	PART NO	NOTES
White 3' Acrylic Diffuser	3054360	
		Don't see the configuration you are looking for? Call us today at (513) 858-6004



TERONLIGHTING.COM 33 DONALD DR, FAIRFIELD, OH 45014 P: 513.858.6004 F: 513.858.6038 E: SALES@TERONLIGHT.COM



We reserve the right to revise the design components of any product due to parts availability or change in UL standards, without assuming any obligation or liability to modify any products previously manufactured, and without notice. 2