ECLIPSE S RNG LED

Architectural Indoor

Ę	(I)	LED	1










FEATURES

- 18 Gauge Steel Fascia w/ Matte Silver Powder Coat Finish
- Luminous White Acrylic w/ White Perf Covering Lens Panel
- Steel Mounting Pan w/ Hi-Reflectance White Powder Coat Finish
- Open Top and Bottom
- Mounts Directly to 4" Junction Box (By Others)
- One 12.6W LED Driver Per 12.5W Module
- 120V Drivers Are Dimmable
- 277V Drivers Are Not Dimmable
- ADA Compliant
- CSA Listed Dry Location For Wall Mounting
- LED Light Fixture
- Mounting Hardware Included

LINE DRAWING



FINISHES

Antique Copper Swedish



TERONLIGHTING.COM

E: SALES@TERONLIGHT.COM

33 DONALD DR, FAIRFIELD, OH 45014

P: 513.858.6004 F: 513.858.6038









Matte Silver







Sand



Contact Teron Lighting Inc.





ECLIPSE S RNG LED

Architectural Indoor



PO#: COMMENTS: QTY:

PROJECT: TYPE:

Fixture Core

PRODUCT CODE	SOURCE/WATTAGE	VOLTAGE	DIMMING DRIVER
ECLS - Eclipse S	L12.5 - (1) 12.5W (40) LED Module L25.0 - (2) 12.5W (40) LED Modules	120V 270V (50 / 60Hz)	Not Applicable
ORDER INFO			
ECLS	L12.5	120V	Not Applicable
Example ^			

Aesthetics & Options

TRIM	FINISH	COLOR TEMP	OPTIONS
RNG - RNG Facia	AC - Antique Copper AS - Antique Silver BT - Bronze Mist MB - Metallic Black SM - Matte Silver (Standard) SN - Sand SW - Swedish Steel	35K - 3500K Color Temp 40K - 4000K Color Temp	F - Fused WAL - White Acrylic
ORDER INFO			
Not Applicable	AC	30K	WAL

Example ^

PROD	SOURCE	30K SPECS
ECLS	L12.5	• 80 CRI Typ. • 30K - 3000K Color Temp • 1195 LED Source Lumens • 95.6 LED Source Lumans Per Watt
	L25.0	• 80 CRI Typ. • 30K - 3000K Color Temp • 2390 LED Source Lumens • 95.6 LED Source Lumans Per Watt

REPLACEMENT PART	PART NO	NOTES	
White Perf Acrylic Lens	3098060	Dimmable to <5%	
White Acrylic Lens	3097660	120V Dimmable With Either Triac or ELV Dimmers	Don't see the configuration you are looking for? Call us today at (513) 858-6004

