FALDO XL LED

Architectural Outdoor








PROJECT:	
TYPE:	
PO#:	QTY:
COMMENTS:	

FEATURES

- Aluminum Housing w/ Textured Black Polyester Powder Coat Finish
- Aluminum Mounting Pan w/ Hi-Reflectance White Powder Coat Finish
- Aluminum Top and Bottom End Plates
- CSA Approved Wet Location For Vertical Mounting
- LED Light Fixture
- Luminous White Acrylic Panels
- Mounts Over 4" Junction Box w/ Easy-hang Wall Mounting Plate (Included)

LINE DRAWING

LINE DRAWING NOT TO SCAL



FINISHES





Antique

Bronze





Sand



For RAL Colors & Custom Match -Contact Teron Lighting Inc.





White

FALDO XL LED

Architectural Outdoor



Fixture Core

PROJECT:	
TYPE:	
PO#:	QTY:
COMMENTS:	·

PRODUCT CODE	SOURCE/WATTAGE	VOLTAGE	DIMMING DRIVER
FLX - Faldo XL ORDER INFO	L19.0-ZE700 - 30W @ 700mA 4-Wire 0-10V Dimming Driver L24.0-ZE875 - 33W @ 875mA 4-Wire 0-10V Dimming Driver L31.0-ZE1150 - 44W @1150mA 4-Wire 0-10V Dimming Driver	120V 277V (50 / 60Hz)	Not Applicable
FLX	L19.0-ZE700	120V	Not Applicable

Example ^ (may not represent a manufacturable product)

Aesthetics & Options

TRIM	FINISH	COLOR TEMP	OPTIONS
Not Applicable	AC - Antique Copper AS - Antique Silver BT - Bronze Mist SM - Matte Silver SN - Sand SW - Swedish Steel TB - Textured Black (Standard)	30K - 3000K Color Temp 35K - 3500K Color Temp 40K - 4000K Color Temp	F - Fused WAL - White Acrylic (Standard)
ORDER INFO			
Not Applicable	AC	30K	ŀ

Example ^ (may not represent a manufacturable product)

PROD	SOURCE	30K SPECS
Faldo X	L19.0	30K - 3000K Color Temp 2489 LED Source Lumens 113 LED Source Lumens Per Watt
	L24.0	30K - 3000K Color Temp 3180 LED Source Lumens 106 LED Source Lumens Per Watt
	L31.0	• 30K - 3000K Color Temp • 4125 LED Source Lumens • 106 LED Source Lumens Per Watt

REPLACEMENT PART	PART NO	NOTES
White Front Acrylic Lens Pane	3028560	
White Side Acrylic Lens Pane	3028660	Don't see the configuration you are looking for? Call us today at (513) 858-6004



FALDO XL LED

Architectural Outdoor





Fixture Core

PROJECT:	
TYPE:	
PO#:	QTY:
COMMENTS:	·

PRODUCT CODE SOURCE/WATTAGE		VOLTAGE DIMMING DRIVER		
FLX - Faldo XL	L38.0-ZE1400 - 50W @ 1400mA 4-Wire 0-10V Dimming Driver L38.0-TE1400 - 60W @ 1400mA ELV Dimming Driver	120V 277V (50 / 60Hz)	Not Applicable	
ORDER INFO				
FLX	L38.0-ZE1400	120V	Not Applicable	

Example ^ (may not represent a manufacturable product)

Aesthetics & Options

TRIM	FINISH	COLOR TEMP	OPTIONS
Not Applicable	AC - Antique Copper AS - Antique Silver BT - Bronze Mist SM - Matte Silver SN - Sand SW - Swedish Steel TB - Textured Black (Standard)	30K - 3000K Color Temp 35K - 3500K Color Temp 40K - 4000K Color Temp	F - Fused WAL - White Acrylic (Standard)
ORDER INFO			
Not Applicable	AC	30K	F

Example ^ (may not represent a manufacturable product)

PROD	SOURCE	30K SPECS		
PROD Faldo X	L38.0	30K SPECS 30K - 3000K Color Temp 4651 LED Source Lumens 116 LED Source Lumens Per Watt 30K - 3000K Color Temp 5208 LED Source Lumens 109 LED Source Lumens Per Watt		

REPLACEMENT PART	PART NO	NOTES
White Front Acrylic Lens Pane	3028560	
White Side Acrylic Lens Pane	3028660	Don't see the configuration you are looking for? Call us today at (513) 858-6004

