


GOLD CUP LG LED



PROJECT :
TYPE :
ORDERING # :
COMMENTS :

FEATURES

- Cast Aluminum Housing w/ Textured Bronze Polyester Powder Coat Finish
- Ribbed Borosilicate Glass Diffuser
- Permlight BB90WB 48W LED Module
- Thomas Research LED50W-48-C1050 50W LED Driver
- Surge Protector
- Fully Gasketed
- Mounts Direct to Flat Surface w/ Four #8 Wall Anchors (Not Included)
- CSA Listed Wet Location For Wall Mount
- L70 Life Time For 50,000hr



ORDERING INFORMATION

Example : (GPL - L48.0 - 100-277V - CGL - SW - 50K)

Textured Bronze is Standard Finish

PRODUCT	SOURCE/WATTAGE	VOLTAGE	DIFFUSER	FINISH	OPTIONS
Gold Cup Lg	L48.0 - 48W LED Module	100 - 277V Please See "Options" Column For Driver Specifications	CGL - Clear Glass Lens (Standard)	SM - Matte Silver TB - Textured Black AC - Antique Copper AS - Antique Silver BT - Bronze Mist SN - Sand SW - Swedish Steel BZ - Textured Bronze TW - Textured White RAL Colors or Custom Match - Consult Factory	40K - 4000K Color Temperature 50K - 5000K Color Temperature DIM - Dimmable Driver (0 - 10V) SDIM - Step-Dimmable Driver (Dimmable to 25% & 50%) PDIM - Pulse Width Dimmable Driver (0 - 10V) MS - Motion Sensor (Can be Used w/ "SDIM" Option) PCL120 - Photocell 120V PCL277 - Photocell 277V LXS - Lexan Lens Shield WGD - Steel Wire Guard TP - Tamper-Proof Screw Set F - Fused EBW - Bodine BSL23 - Will light Two 5.5W LED Strips - Average 340 Source Lumens EBC - Bodine BSL10 - Will light Two 5.5W LED Strips - Estimated 1236 Source Lumens Please Note: 120V or 277V Must Be Specified When Ordering The EB Or PCL Option

NOTES

We reserve the right to revise the design or components of any product due to parts availability or change in UL standards, without assuming any obligation or liability to modify any products previously manufactured, and without notice.

REPLACEMENT PARTS

PART NO.

Ribbed Borosilicate Glass Diffuser	37129
Frosted Ribbed Borosilicate Glass Diffuser	3712962

ARRA 2009



BUY AMERICA ACT





PROJECT :
TYPE :
ORDERING # :
COMMENTS :

PRODUCT	SOURCE/WATTAGE	40K SPECIFICATIONS	50K SPECIFICATIONS
Gold Cup LG LED	L48.0 - (1) 48W LED Board	LED Specifications - 90 LEDs Per Strip - SW50Bin, Color Temp = 4000K Nominal - Constant Current at 1050mA by Driver - 80 CRI typ. (75 CRI min) 5368 Lumens - 58W Input = Estimated 93 Lumens Per Watt	LED Specifications - 90 LEDs Per Strip - SW50Bin, Color Temp = 5000K Nominal - Constant Current at 1050mA by Driver - 80 CRI typ. (75 CRI min) 5650 Lumens - 58W Input = Estimated 97 Lumens Per Watt

