

OVERLAND LED 36"

Architectural Indoor



PROJECT:	
TYPE:	
PO#:	QTY:
COMMENTS:	




FEATURES


- Steel Housing w/ White Powder Coat Finish
- Steel Mounting Pan w/ Hi-Reflectance White Powder Coat Finish
- Steel End Caps w/ White Powder Coat Finish
- Clear Ribbed Acrylic Lens
- Up / Down Lighting
- Mounts Directly to Surface w/ Two Wall Anchors (Not Included)
- Convenience Outlet Available
- Pull Chain Available
- IES Files Available
- CSA Listed Damp Location, Including All Options Except For EB
- Emergency Battery Available
- LED Light Fixture

LINE DRAWING

LINE DRAWING NOT TO SCALE



FINISHES



OVERLAND LED 36"

Architectural Indoor



Fixture Core

PROJECT:	
TYPE:	
PO#:	QTY:
COMMENTS:	

PRODUCT CODE	SOURCE/WATTAGE	VOLTAGE	DIMMING DRIVER
OLD36 - Overland 36"	L43.5-LE1280 - 43.5W @ 1280mA Triac Dimming Driver* L54.4-LE1600 - 54.4W @ 1600mA Triac Dimming Driver* L54.4-ZE1600 - 54.4W @ 1600mA Line Voltage 4-Wire Dimming Driver (Dimmable 0 - 10V)	120V 277V (50 / 60Hz)	Not Applicable
ORDER INFO			
OLD36 Example ^	L43.5-LE1280	120V	Not Applicable

Aesthetics & Options

TRIM	FINISH	COLOR TEMP	OPTIONS
Not Applicable	AC - Antique Copper AS - Antique Silver BT - Bronze Mist BN - Brushed Nickel SM - Matte Silver MB - Metallic Black SN - Sand SW - Swedish Steel TB - Textured Black BZ - Textured Bronze TW - Textured White WH - Gloss White (Standard)	30K - 3000K Color Temp 35K - 3500K Color Temp 40K - 4000K Color Temp	2SW - Dual Switch w/ Pull Chain* BFL - Front Baffle For Up / Down Lighting CO - Convenience Outlet* EB - Integral Emergency Battery (Not Available For SD10)** F - Fused DIV - Internal Divider For Up/Down Lighting (Recommended For Use With MSW + 25W Option) DL - Downlight Only, MSW - Multi Switch w/ Pull Chain (120V Only) (For Up, Down, and Up / Down Light) NLT - 5.1W LED Night Light**
ORDER INFO			
Not Applicable Example ^	AC	30K	2SW

PROD	SOURCE	30K SPECS			
OLD 36"	L43.5	<ul style="list-style-type: none"> 30K - 3000K Color Temp 5150 LED Source Lumens 125.6 LED Source Lumens Per Watt 			
	L54.4	<ul style="list-style-type: none"> 30K - 3000K Color Temp 7802 LED Source Lumens 123.8 LED Source Lumens Per Watt 			

REPLACEMENT PART	PART NO	NOTES
36" Clear Acrylic (3 Lamp) Diffuser	30048	* Option is for 120V Only

Don't see the configuration you are looking for?
Call us today at (513) 858-6004



TERONLIGHTING.COM
 33 DONALD DR, FAIRFIELD, OH 45014
 P: 513.858.6004 F: 513.858.6038
 E: SALES@TERONLIGHT.COM



We reserve the right to revise the design components of any product due to parts availability or change in UL standards, without assuming any obligation or liability to modify any products previously manufactured, and without notice.