

KATONA BFP LED 36"

Architectural Indoor



PROJECT:	
TYPE:	
PO#:	QTY:
COMMENTS:	



FEATURES

- Die-Formed Cold-Rolled Steel Housing
- Anodized Aluminum Reflector
- Acrylic Lens
- Mounts Directly to 4" Junction Box (By Others)
- Energy Star
- ETL/cETL Listed Dry Location
- LED Light Fixture
- Mounting Hardware Included



LINE DRAWING

LINE DRAWING NOT TO SCALE



FINISHES

Brushed
Nickel



KATONA BFP LED 36"

Architectural Indoor



Fixture Core

PROJECT:	
TYPE:	
PO#:	QTY:
COMMENTS:	

PRODUCT CODE	SOURCE/WATTAGE	VOLTAGE	DIMMING DRIVER
KA36 - Katona 36"	L23.0-700 - (1) 23W @ 700mA	120V - 277V	Not Applicable
ORDER INFO			
KA36 Example ^	L23.0-700	120/277V	Not Applicable

Aesthetics & Options

TRIM	FINISH	COLOR TEMP	OPTIONS
Not Applicable	BN - Brushed Nickel (Standard)	30K - 3000K Color Temp. 40K - 4000K Color Temp.	Not Applicable
ORDER INFO			
Not Applicable Example ^	BN	30K	Not Applicable

PROD	SOURCE	30K SPECS	40K SPECS
KA36	L23.0	<ul style="list-style-type: none"> 30K - 3000K Color Temp 2426 LED Source Lumens 101 LED Source Lumens Per Watt 	<ul style="list-style-type: none"> 40K - 4000K Color Temp 1999 LED Source Lumens 84 LED Source Lumens Per Watt

REPLACEMENT PART	PART NO	NOTES
		KA36 L70 >50,000 hrs Minimum Starting Temperature = -20 Degrees C



TERONLIGHTING.COM
 33 DONALD DR, FAIRFIELD, OH 45014
 P: 513.858.6004 F: 513.858.6038
 E: SALES@TERONLIGHT.COM

We reserve the right to revise the design components of any product due to parts availability or change in UL standards, without assuming any obligation or liability to modify any products previously manufactured, and without notice.