KATONA LED 24"

Architectural Indoor











FEATURES

- Acrylic Lens
- · Anodized Aluminum Reflector
- Die-formed Cold-rolled Steel Housing
- Energy Star
- ETL/cETL Listed Dry Location
- LED Light Fixture
- Mounting Hardware Included
- Mounts Directly to 4" Junction Box (By Others)


PROJECT: TYPE:

COMMENTS:

PO#:

LINE DRAWING

QTY:



FINISHES

Brushed Nickel





KATONA LED 24"

Architectural Indoor









שוז	LED	7	-English
Lures		7	ENERGY STAF

Fixture Core

PRODUCT CODE	SOURCE/WATTAGE	VOLTAGE	DIMMING DRIVER
KA - Katona	L19.0-LT500 - 19.0W @ 500mA Constant Current	120V	TRIAC - Triac Dimming Driver
ORDER INFO			
KA	L19.0-LT500	120V	TRIAC
Example ^			

PROJECT: TYPE:

COMMENTS:

PO#:

Aesthetics & Options

TRIM	FINISH	COLOR TEMP	OPTIONS
Not Applicable	BN - Brushed Nickel (Standard)	30K - 3000K Color Temp. 40K - 4000K Color Temp.	Not Applicable
ORDER INFO			
Not Applicable	BN	30K	Not Applicable

PROD	SOURCE	30K SPECS	40K SPECS		
KA	L19.0	30K SPECS 30K - 3000K Color Temp 1540 LED Source Lumens 90.6 LED Source Lumens Per Watt	40K SPECS 40K-4000K Color Temp 1256 LED Source Lumens 90.4 LED Source Lumens Per Watt		

REPLACEMENT PART PART NO	
DEDIAMENT DADI I DADI NI	

NOTES

L70 >36,000 hrs

Minimum Starting Temperature = -20 Degrees C

Don't see the configuration you are looking for? Call us today at (513) 858-6004

QTY:



