KATONA LED 36"

Architectural Indoor






PROJECT: TYPE: PO#: COMMENTS:

QTY:

FEATURES

- Acrylic Lens
- Anodized Aluminum Reflector
- · Die-formed Cold-rolled Steel Housing
- Energy Star
- ETL/cETL Listed Dry Location
- LED Light Fixture
- Mounting Hardware Included
- Mounts Directly to 4" Junction Box (By Others)

LINE DRAWING



FINISHES

Brushed Nickel





TERONLIGHTING.COM 33 DONALD DR, FAIRFIELD, OH 45014 P: 513.858.6004 F: 513.858.6038 E: SALES@TERONLIGHT.COM



We reserve the right to revise the design components of any product due to parts availability or change in UL standards, without assuming any obligation or liability to modify any products previously manufactured, and without notice.

KATONA LED 36"

Architectural Indoor

(1)

PROJECT:	
TYPE:	
PO#:	QTY:
COMMENTS:	

-44169-	_	

PRODUCT CODE	SOURCE/WATTAGE	VOLTAGE	DIMMING DRIVER
KA - Katona	L23.0-700 - 23.0W @ 700mA Constant Current	1200 - 2770	Not Applicable
DRDER INFO			
	L23.0-700	120V-277V	Not Applicable

Aesthetics & Options

	FINISH	COLOR TEMP	OPTIONS
Not Applicable	BN - Brushed Nickel (Standard)	30K - 3000K Color Temp. 40K - 4000K Color Temp.	Not Applicable
ORDER INFO			

Example ^

PROD SOURCE 30K SPECS 40K SPECS	
KA L23.0 • 30K - 3000K Color Temp • 2426 LED Source Lumens • 40K- 4000K Color Temp • 1999 LED Source Lumens • 101.1 LED Source Lumens Per Watt • 40K- 4000K Color Temp • 1999 LED Source Lumens • 30K - 3000K Color Temp • 1999 LED Source Lumens	

REPLACEMENT PART

NOTES L70 >50,000 hrs

Minimum Starting Temperature = -20 Degrees C

Don't see the configuration you are looking for? Call us today at (513) 858-6004



TERONLIGHTING.COM 33 DONALD DR, FAIRFIELD, OH 45014 P: 513.858.6004 F: 513.858.6038 E: SALES@TERONLIGHT.COM



We reserve the right to revise the design components of any product due to parts availability or change in UL standards, without assuming any obligation or liability to modify any products previously manufactured, and without notice.