## KATONA MCT LED 24"

Architectural Indoor

ÆTI)	
クログ	L














#### **FEATURES**

- Acrylic Lens
- · Anodized Aluminum Reflector
- Die-formed Cold-rolled Steel Housing
- Energy Star
- ETL/cETL Listed Dry Location
- LED Light Fixture
- MCT 3000k, 3500k, 4000k
- Mounting Hardware Included
- Mounts Directly to 4" Junction Box (By Others)

#### LINE DRAWING



### **FINISHES**

Brushed Nickel







# KATONA MCT LED 24"

Architectural Indoor







Fixture Core

PROJECT:	
TYPE:	
PO#:	QTY:
COMMENTS:	·

PRODUCT CODE	SOURCE/WATTAGE	VOLTAGE	DIMMING DRIVER
KA - Katona L19.0-LT500 - 19.0W @ 500mA Constant Current		120V	TRIAC - Triac Dimming Driver
ORDER INFO			
КА	L19.0-LT500	120V	TRIAC
Example ^			

Aesthetics & Options

TRIM	FINISH	COLOR TEMP	OPTIONS
Not Applicable	<b>BN</b> - Brushed Nickel (Standard)	MCT - 3000K, 3500K, 4000K Color Temp.	Not Applicable
ORDER INFO			
Not Applicable	BN	MCT	Not Applicable

PROD	SOURCE	30K SPECS	40K SPECS		
KA	L19.0	30K SPECS  30K - 3000K Color Temp 1540 LED Source Lumens 90.6 LED Source Lumens Per Watt	40K SPECS  40K-4000K Color Temp 1256 LED Source Lumens 90.4 LED Source Lumens Per Watt		

REPLACEMENT PART	PART NO	NOTES	
		L70 >36,000 hrs	
		Minimum Starting Temperature = -20 Degrees C	Don't see the configuration you are looking for? Call us today at (513) 858-6004

