KATONA MCT LED 36"

Architectural Indoor














PROJECT:			
TYPE:			
PO#:	QTY:		
COMMENTS:			

FEATURES

- Acrylic Lens
- · Anodized Aluminum Reflector
- Die-formed Cold-rolled Steel Housing
- Energy Star
- ETL/cETL Listed Dry Location
- LED Light Fixture
- MCT 3000k, 3500k, 4000k
- Mounting Hardware Included
- Mounts Directly to 4" Junction Box (By Others)

LINE DRAWING



FINISHES

Brushed Nickel







KATONA MCT LED 36"

Architectural Indoor









energy	
ENERGY STAR	

Fixture Core

PRODUCT CODE	SOURCE/WATTAGE	VOLTAGE	DIMMING DRIVER	
KA - Katona	L23.0-700 - 23.0W @ 700mA Constant Current	120V - 277V	Not Applicable	
ORDER INFO				
KA	L23.0-700	120V-277V	Not Applicable	
Example ^				

PROJECT: TYPE:

COMMENTS:

PO#:

Aesthetics & Options

TRIM	FINISH	COLOR TEMP	OPTIONS
Not Applicable	BN - Brushed Nickel (Standard)	MCT - 3000K, 3500K, 400 Color Temp.	Not Applicable
ORDER INFO			
Not Applicable	BN	MCT	Not Applicable

PROD	SOURCE	30K SPECS	40K SPECS		
KA	L23.0	OK SPECS OUT To Suppose the suppose of the suppos	40K SPECS 40K-4000K Color Temp 1999 LED Source Lumens 84 LED Source Lumens Per Watt		

	NT PART	I PART N

NOTES

L70 >50,000 hrs

Minimum Starting Temperature = -20 Degrees C

Don't see the configuration you are looking for? Call us today at (513) 858-6004

QTY:



