# KATONA MCT LED 48"

Architectural Indoor

(TI)	LE









### **FEATURES**

- Acrylic Lens
- · Anodized Aluminum Reflector
- Die-formed Cold-rolled Steel Housing
- Energy Star
- ETL/cETL Listed Dry Location
- LED Light Fixture
- MCT 3000k, 3500k, 4000k
- Mounting Hardware Included
- Mounts Directly to 4" Junction Box (By Others)


PROJECT: TYPE:

COMMENTS:

PO#:

#### LINE DRAWING

QTY:



### **FINISHES**

Brushed Nickel





# KATONA MCT LED 48"

Architectural Indoor









Fi	x†	ur	е	Cc	r	е.	

rixture core				
PRODUCT CODE	SOURCE/WATTAGE	VOLTAGE	DIMMING DRIVER	
KA - Katona  L38.0-1050 - 38.0W @ 1050mA Constant Current		120V - 277V	Not Applicable	
ORDER INFO				
KA	L38.0-1050	120V-277V	Not Applicable	
Evample ^				

PROJECT: TYPE:

COMMENTS:

PO#:

Aesthetics & Options

TRIM	FINISH	COLOR TEMP	OPTIONS
Not Applicable	<b>BN</b> - Brushed Nickel (Standard)	MCT - 3000K, 3500K, 4000 Color Temp.	Not Applicable
ORDER INFO			
Not Applicable  Example ^	BN	MCT	Not Applicable

PROD	SOURCE	30K SPECS	40K SPECS		
KA	L38.0	30K SPECS     30K - 3000K     Color Temp     3477 LED     Source Lumens     96.6 LED Source     Lumens Per Watt	40K SPECS      40K-4000K     Color Temp     3037 LED     Source Lumens     86.8 LED Source     Lumens Per Watt		

REPLACEM	I PART NO

NOTES

L70 >36,000 hrs

Minimum Starting Temperature = -20 Degrees C

Don't see the configuration you are looking for? Call us today at (513) 858-6004

QTY:



