

# MESA BFP LED 15"

Architectural Indoor



PROJECT:	
TYPE:	
PO#:	QTY:
COMMENTS:	


## FEATURES

- Die-Formed Cold-Rolled Steel Housing
- Anodized Aluminum Reflector
- Fabric Lens with Acrylic Bottom
- Mounts Directly to 4" Junction Box (By Others)
- Energy Star
- Damp Location
- ETL/cETL Listed
- LED Light Fixture



## LINE DRAWING

LINE DRAWING NOT TO SCALE



## FINISHES

Brushed  
Nickel



# MESA BFP LED 15"

Architectural Indoor



Fixture Core

PROJECT:	
TYPE:	
PO#:	QTY:
COMMENTS:	

PRODUCT CODE	SOURCE/WATTAGE	VOLTAGE	DIMMING DRIVER
<b>MSA15 - Mesa 15"</b>	<b>L24.0-700 - (1) 24W @ 700mA</b>	<b>120V - 277V</b>	<b>Not Applicable</b>
ORDER INFO			
MSA15 Example ^	L24.0-700	120/277V	Not Applicable

Aesthetics & Options

TRIM	FINISH	COLOR TEMP	OPTIONS
<b>Not Applicable</b>	<b>BN - Brushed Nickel (Standard)</b>	<b>30K - 3000K Color Temp. 40K - 4000K Color Temp.</b>	<b>FM - Flush Mount PM - Pendant Mount (6" Stem)</b>
ORDER INFO			
Not Applicable Example ^	BN	30K	FM

PROD	SOURCE	30K SPECS				
<b>MSA15</b>	L24.0	<ul style="list-style-type: none"> <li>• 30K - 3000K Color Temp</li> <li>• 1997 LED Source Lumens</li> <li>• 108.3 LED Source Lumens Per Watt</li> <li>• 80 CRI</li> </ul>				

REPLACEMENT PART	PART NO	NOTES
		L70 >35,000 hrs Minimum Starting Temperature = -20 Degrees C



TERONLIGHTING.COM  
 33 DONALD DR, FAIRFIELD, OH 45014  
 P: 513.858.6004 F: 513.858.6038  
 E: SALES@TERONLIGHT.COM

We reserve the right to revise the design components of any product due to parts availability or change in UL standards, without assuming any obligation or liability to modify any products previously manufactured, and without notice.