Architectural Indoor

SB	LED	*

	PROJECT:	
ſ	TYPE:	
	PO#:	QTY:
I	COMMENTS:	




#### **FEATURES**

- CSA Listed Damp Location Wall and Ceiling
- LED Light Fixture
- Luminous Acrylic Diffuser
- Mounts Directly to 4" Junction Box (By Others)
- Mounting Hardware Included
- Steel Mounting Pan w/ Hi-Reflectance White Powder Coat Finish

### LINE DRAWING

LINE DRAWING NOT TO SCALE













For RAL Colors & Custom Match -Contact Teron Lighting Inc.





Architectural Indoor



PROJECT:	
TYPE:	
PO#:	QTY:
COMMENTS:	

Fixture Core

PRODUCT CODE	SOURCE/WATTAGE	VOLTAGE	DIMMING DRIVER	
HPMS - Hollywood Park Medium Sconce  L12.5-LT350 - 12.5W @350mA 2-Wire Trailing or Leading Edge Dimming Driver L12.5-ZE350 - 12.5W @350mA 4-Wire Dimming Driver (Dimmable 0 - 10V)		<b>120V 270V</b> (50 / 60Hz)	Not Applicable	
ORDER INFO	,			
HPMS	L12.5	120V	Not Applicable	
Example ^				

Aesthetics & Options

TRIM	FINISH	COLOR TEMP	OPTIONS
Not	BLF - Bleached Linen Fabric	<b>30K</b> - 3000K Color Temp	<b>F</b> - Fused
Applicable	CLF - Cream Linen Fabric	<b>35K</b> - 3500K Color Temp	LC- Laminate Coating (See
	TEF - Textured Eggshell Fabric	<b>40K</b> - 4000K Color Temp	Notes Below)
	ESF - Espresso Linen Fabric		
	PLF - Platinum Linen Fabric		
ORDER INFO			
Not Applicable	BLF	30K	F

Example ^

PROD	SOURCE	30K SPECS		
HPMS	L12.5	80 CRI Typ.     30K - 3000K     Color Temp     1195 LED     Source Lumens     95.6 LED Source     Lumens Per Watt		

REPLACEMENT PART	PART NO
------------------	---------

HPMS-Platinum Linen Fabric HPMS-Textured Eggshell Fabric HPMS-Espresso Linen Fabric HPMS-Cream Linen Fabric HPMS-Bleached Linen Fabric

#### NOTES

\* Laminate Coating allows Lens to be easily wiped down with damp cloth. Not applicable to Textured Eggshell as it comes standard with Laminate Coating.

Don't see the configuration you are looking for? Call us today at (513) 858-6004





Architectural Indoor



PROJECT:	
TYPE:	
PO#:	QTY:
COMMENTS:	

Fixture Core

PRODUCT CODE	SOURCE/WATTAGE	VOLTAGE	DIMMING DRIVER
<b>HPMS</b> - Hollywood Park Medium Sconce	L15.0-LT400 - 15.0W @400mA 2-Wire Trailing or Leading Edge Dimming L25.0-LT500 - 25.0W @500mA 2-Wire Trailing or Leading Edge Dimming	120V 270V (50 / 60Hz)	Not Applicable
ORDER INFO	5		
HPMS	L15.0	120V	Not Applicable
Example ^			

Aesthetics & Options

TRIM	FINISH	COLOR TEMP	OPTIONS
Not	BLF - Bleached Linen Fabric	<b>30K</b> - 3000K Color Temp	<b>F</b> - Fused
Applicable	CLF - Cream Linen Fabric	<b>35K</b> - 3500K Color Temp	LC- Laminate Coating (See
	TEF - Textured Eggshell Fabric	<b>40K</b> - 4000K Color Temp	Notes Below)
	ESF - Espresso Linen Fabric		
	PLF - Platinum Linen Fabric		
ORDER INFO			
Not Applicable	BLF	30K	F

Example ^

PROD	SOURCE	BOK SPECS
HPMS	L15.0	• 80 CRI Typ. • 30K - 3000K Color Temp • 2390 LED Source Lumens • 95.6 LED Source Lumens Per Watt
	L25.0	• 80 CRI Typ. • 30K - 3000K Color Temp • 2390 LED Source Lumens • 95.6 LED Source Lumens Per Watt

REPLACEMENT PART	PART NO

HPMS-Platinum Linen Fabric HPMS-Textured Eggshell Fabric HPMS-Espresso Linen Fabric HPMS-Cream Linen Fabric HPMS-Bleached Linen Fabric

#### NOTES

\* Laminate Coating allows Lens to be easily wiped down with damp cloth. Not applicable to Textured Eggshell as it comes standard with Laminate Coating.

Don't see the configuration you are looking for? Call us today at (513) 858-6004





Architectural Indoor



TYPE:	
PO#:	QTY:
COMMENTS:	

Fixture Core

PRODUCT CODE	SOURCE/WATTAGE	VOLTAGE	DIMMING DRIVER
HPMS - Hollywood Park Medium Sconce	L25.0-ZE500 - 25.0W @500mA 4-Wire Dimming Driver (Dimmable 0 - 10V)	<b>120V 270V</b> (50 / 60Hz)	Not Applicable
ORDER INFO			
HPMS	L25.0	120V	Not Applicable
Example ^			

PROJECT:

Aesthetics & Options

BLF - Bleached Linen Fabric CLF - Cream Linen Fabric TEF - Textured Eggshell Fabric ESF - Espresso Linen Fabric	<b>30K</b> - 3000K Color Temp <b>35K</b> - 3500K Color Temp <b>40K</b> - 4000K Color Temp	<b>F</b> - Fused <b>LC</b> - Laminate Coating (See Notes Below)
TEF - Textured Eggshell Fabric	'	_ ·
Fabric	<b>40K</b> - 4000K Color Temp	Notes Below)
ESF - Espresso Linen Fabric		
PLF - Platinum Linen Fabric		
_	BLF	

Example ^

PROD	SOURCE	30K SPECS		
PROD HPMS	L25.0	80 CRI Typ.     30K - 3000K     Color Temp     2390 LED     Source Lumens     95.6 LED Source     Lumens Per Watt		

REPLACEMENT PART   F	PART NO

HPMS-Platinum Linen Fabric HPMS-Textured Eggshell Fabric HPMS-Espresso Linen Fabric HPMS-Cream Linen Fabric HPMS-Bleached Linen Fabric

#### NOTES

\* Laminate Coating allows Lens to be easily wiped down with damp cloth. Not applicable to Textured Eggshell as it comes standard with Laminate Coating.

Don't see the configuration you are looking for? Call us today at (513) 858-6004



