SONATA LED

Architectural Indoor


کے	LED	7
		1

PROJECT:		
TYPE:		
PO#:	QTY:	
COMMENTS:		

FEATURES

- ADA Compliant
- Aluminum Fascia, Arm & Mount Pan w/ Standard Matte Silver Powder Coat Finish
- Aluminum Mounting Plate Mounts to Wall Surface (Offset Over and Attached to J-Box)
- CSA Listed Dry Location for Wall Mount
- Indirect Lighting Source
- Leading and Trailing Edge Dimmable
- LED Light Fixture
- UL Class 2 Driver

LINE DRAWING



FINISHES

TERONLIGHTING.COM















For RAL Colors & Custom Match -**Contact Teron** Lighting Inc.







SONATA LED

Architectural Indoor



PROJECT:	
TYPE:	
PO#:	QTY:
COMMENTS:	

Fixture Core

PRODUCT CODE	SOURCE/WATTAGE	VOLTAGE	DIMMING DRIVER	
SNA - Sonata LED	L20.0-LT700 - 20.0W @ 700mA Leading and Trailing Edge Dimming L17.1-LT600 - 17.1W @ 600mA Leading and Trailing Edge Dimming L10.0-LT350 - 10.0W @ 350mA Leaging and Trailing Edge Dimming	120-277V (50/60Hz)	LT - Leading and Trailing Edge Dimming	
ORDER INFO				
SNA Example ^	L20.0-LT700	120-277V	Not Applicable	

Aesthetics & Options

TRIM	FINISH	COLOR TEMP	OPTIONS
Not Applicable	AC - Antique Copper AS - Antique Silver BT - Bronze Mist SM - Matte Silver (Standard) SN - Sand SW - Swedish Steel TB - Textured Black	30K - 3000K Color Temp 35K - 3500K Color Temp 40K - 4000K Color Temp 50K - 5000K Color Temp	SP - Surge Protector
ORDER INFO			
Not Applicable	AC	30K	SP

PROD	SOURCE	30K SPECS	40K SPECS	50K SPECS	
SNA	L20.0	OK SPECS OUT TO SOUR COLOR TEMP 2280 LED SOURCE LUMENS 114 LED SOURCE LUMENS PER WATT	40K SPECS 40K - 4000K Color Temp 2324 LED Source Lumens 116 LED Source Lumens Per Watt	50K SPECS 50K - 5000K Color Temp 2372 LED Source Lumens 118 LED Source Lumens Per Watt	

REPLACEMENT PART	PART NO
------------------	---------

NOTES

Don't see the configuration you are looking for? Call us today at (513) 858-6004

