# ARIES SMALL SINGLE RING LED

Architectural Indoor

### **FEATURES**

- Acrylic Lens
- Aluminum and Steel Construction

PROJECT: TYPE:


COMMENTS:

PO#:

- CRI  $\ge$  90
- Dimmable @ 120V
- Dimmable to 10%
- ETL Listed
- LED Light Fixture
- 120 Volt
- ~50,000 Hour Rated LED Life

#### LINE DRAWING

LINE DRAWING NOT TO SCALE



### **FINISHES**

Brushed Champagne





 TERONLIGHTING.COM

 33 DONALD DR, FAIRFIELD, OH 45014

 P: 513.858.6004

 F: 513.858.6038

 E: SALES@TERONLIGHT.COM

QTY:

# ARIES SMALL SINGLE RING LED

Architectural Indoor

### 

PROJECT:	
TYPE:	
PO#:	
COMMENTS:	

QTY:

Fixture Core SOURCE/WATTAGE VOLTAGE **DIMMING DRIVER** PRODUCT CODE ASSR- Aries Small Single Ring L41.0-LT1400 - 41W @ 120V ELV or TRIAC Dimming @ 120V LED 1400mA ELV Low Voltage 2-Wire Dimming Electronic Driver (Leading or Trailing Edge) ORDER INFO

Example ^

Aesthetics & Options

TRIM		FINISH	COLOR TEMP		OPTIONS	
Not Appli	cable	BC - Brushed Champagne	<b>30K</b> - 3000K Color	Temp	Not Applicable	
ORDER INFO						
		<b>D</b> 0	201/		Net AverBerkler	
Not Applica Example ^	ble	BC	30K		Not Applicable	
PROD	SOURCE	30K SPECS				
ASSR	L41.0	<ul> <li>30K - 3000K Color Temp</li> <li>3120 LED Source Lumens</li> <li>76 LED Source Lumens Per Watt</li> </ul>				

NOTES

Don't see the configuration you are looking for? Call us today at (513) 858-6004



TERONLIGHTING.COM 33 DONALD DR, FAIRFIELD, OH 45014 P: 513.858.6004 F: 513.858.6038 E: SALES@TERONLIGHT.COM

• 719 Delivered LED Lumens • 17.5 Delivered LED Lumens Per Watt

> We reserve the right to revise the design components of any product due to parts availability or change in UL standards, without assuming any obligation or liability to modify any products previously manufactured, and without notice. 2