

# LYNX ROUND 29.5" LED

Architectural Indoor




PROJECT:	
TYPE:	
PO#:	QTY:
COMMENTS:	

## FEATURES

- Acrylic Lens
- Aluminum Construction
- ADA Compliant
- Ceiling or Wall Mounted
- CRI  $\geq$  90
- Dimmable @ 120V
- Dimmable to 10%
- ETL Listed For Dry Locations
- LED Light Fixture
- 120V
- ~50,000 Hour Rated LED Life

## LINE DRAWING

LINE DRAWING NOT TO SCALE



## FINISHES

Satin Dark  
Gray



# LYNX ROUND 29.5" LED

Architectural Indoor



Fixture Core

PROJECT:	
TYPE:	
PO#:	QTY:
COMMENTS:	

PRODUCT CODE	SOURCE/WATTAGE	VOLTAGE	DIMMING DRIVER
<b>LXR29.5</b> - Lynx Round 29.5" LED	<b>L64.0-LT1800</b> - 64W @ 1800mA ELV Low Voltage 2-Wire Dimming Electronic Driver (Leading or Trailing Edge)	<b>120V</b>	<b>ELV or TRIAC Dimming @ 120V</b>
ORDER INFO			
LXR29.5 Example ^	L64.0-LT1800	120V	ELV, TRIAC

## Aesthetics & Options

TRIM	FINISH	COLOR TEMP	OPTIONS
<b>Not Applicable</b>	<b>SDG</b> - Satin Dark Gray	<b>30K</b> - 3000K Color Temp	<b>Not Applicable</b>
ORDER INFO			
Not Applicable Example ^	SDG	30K	Not Applicable

PROD	SOURCE	30K SPECS				
<b>LXR29.5</b>	L64.0	<ul style="list-style-type: none"> <li>• 30K - 3000K Color Temp</li> <li>• 4590 LED Source Lumens</li> <li>• 71.7 LED Source Lumens Per Watt</li> </ul>				

## NOTES

Don't see the configuration you are looking for?  
Call us today at (513) 858-6004



**TERONLIGHTING.COM**  
33 DONALD DR, FAIRFIELD, OH 45014  
P: 513.858.6004 F: 513.858.6038  
E: SALES@TERONLIGHT.COM

We reserve the right to revise the design components of any product due to parts availability or change in UL standards, without assuming any obligation or liability to modify any products previously manufactured, and without notice.