

# METRO LARGE SINGLE LED

Architectural Indoor



PROJECT:	
TYPE:	
PO#:	QTY:
COMMENTS:	




## FEATURES

- Acrylic Lens
- Ceiling Mounted
- CRI  $\geq$  90
- Dimmable @ 120V
- Dimmable to 10%
- ETL Listed For Dry Locations
- LED Light Fixture
- Polyurethane and Steel Construction
- 120V
- ~50,000 Hour Rated LED Life

## LINE DRAWING

LINE DRAWING NOT TO SCALE



## FINISHES

Matte White



# METRO LARGE SINGLE LED

Architectural Indoor



Fixture Core

PROJECT:	
TYPE:	
PO#:	QTY:
COMMENTS:	

PRODUCT CODE	SOURCE/WATTAGE	VOLTAGE	DIMMING DRIVER
<b>MTLS - Metro Large Single LED</b>	<b>L52.0-LT2100 - 52W @ 2100mA ELV Low Voltage 2-Wire Dimming Electronic Driver (Leading or Trailing Edge)</b>	<b>120V</b>	<b>ELV or TRIAC Dimming @ 120V</b>
ORDER INFO			
MTLS	L52.0-LT2100	120V	ELV, TRIAC

Example ^

Aesthetics & Options

TRIM	FINISH	COLOR TEMP	OPTIONS
<b>Not Applicable</b>	<b>MH - Matte White</b>	<b>30K - 3000K Color Temp</b>	<b>Not Applicable</b>
ORDER INFO			
Not Applicable	MH	30K	Not Applicable

Example ^

PROD	SOURCE	30K SPECS				
<b>MTLS</b>	<b>L52.0</b>	<ul style="list-style-type: none"> <li>• 30K - 3000K Color Temp</li> <li>• 5040 LED Source Lumens</li> <li>• 96.9 LED Source Lumens Per Watt</li> <li>• 2205 Delivered LED Lumens</li> <li>• 42.4 Delivered LED Lumens Per Watt</li> </ul>				

## NOTES

Don't see the configuration you are looking for?  
Call us today at (513) 858-6004



**TERONLIGHTING.COM**  
33 DONALD DR, FAIRFIELD, OH 45014  
P: 513.858.6004 F: 513.858.6038  
E: SALES@TERONLIGHT.COM

We reserve the right to revise the design components of any product due to parts availability or change in UL standards, without assuming any obligation or liability to modify any products previously manufactured, and without notice.