


# AREGA SMALL LED

Architectural Indoor



PROJECT:	
TYPE:	
PO#:	QTY:
COMMENTS:	




## FEATURES

- Acrylic Lens
- Adjustable Cable
- Aluminum Construction
- Ceiling Mounted
- CRI  $\geq$  90
- Dimmable @ 120V (100% - 10%)
- Dimming Driver Contained In Canopy
- ETL Listed For Dry Locations
- LED Light Fixture
- 120V Only
- 2" Recommended Minimum Cable Length; Max Fixture Length 154.1"
- ~50,000 Hour Rated LED Life

## LINE DRAWING

LINE DRAWING NOT TO SCALE



## FINISHES

Satin Dark  
Gray



# AREGA SMALL LED

Architectural Indoor



Fixture Core

PROJECT:	
TYPE:	
PO#:	QTY:
COMMENTS:	

PRODUCT CODE	SOURCE/WATTAGE	VOLTAGE	DIMMING DRIVER
<b>ARS</b> - Arega Small LED	<b>L72.0-LT2400</b> - 72W LED @ 700mA ELV Low Voltage 2-Wire Dimming Electronic Driver (Leading or Trailing Edge)	<b>120V</b>	<b>ELV or TRIAC Dimming @ 120V</b>
ORDER INFO			
ARS	L72.0-LT2400	120V	ELV, TRIAC

Example ^

Aesthetics & Options

TRIM	FINISH	COLOR TEMP	OPTIONS
<b>Not Applicable</b>	<b>SDG</b> - Satin Dark Gray	<b>30K</b> - 3000K Color Temp	<b>Not Applicable</b>
ORDER INFO			
Not Applicable	SDG	20K	Not Applicable

Example ^

PROD	SOURCE	30K SPECS				
<b>ARS</b>	L72.0	<ul style="list-style-type: none"> <li>• 30K - 3000K Color Temp</li> <li>• 6300 LED Source Lumens</li> <li>• 87.5 LED Source Lumens Per Watt</li> </ul>				

## NOTES

Don't see the configuration you are looking for?  
Call us today at (513) 858-6004



**TERONLIGHTING.COM**  
33 DONALD DR, FAIRFIELD, OH 45014  
P: 513.858.6004 F: 513.858.6038  
E: SALES@TERONLIGHT.COM

We reserve the right to revise the design components of any product due to parts availability or change in UL standards, without assuming any obligation or liability to modify any products previously manufactured, and without notice.