

CADET LARGE BFP LED

Architectural Indoor



PROJECT:	
TYPE:	
PO#:	QTY:
COMMENTS:	


FEATURES

- ADA Compliant
- Class 2 LED Driver: 120V - 277V
- CRI > 80
- Die-Formed Cold-Rolled Steel Housing
- ETL/cETL Listed For Damp Locations
- LED Light Fixture
- High Transmission Acrylic Optical Shade
- UL Listed
- Wall Mounted
- 5 Years Warranty on Driver and LED Module



LINE DRAWING


LINE DRAWING NOT TO SCALE



FINISHES

Oil Rubbed
Bronze

Satin Nickel



CADET LARGE BFP LED

Architectural Indoor



Fixture Core

PROJECT:	
TYPE:	
PO#:	QTY:
COMMENTS:	

PRODUCT CODE	SOURCE/WATTAGE	VOLTAGE	DIMMING DRIVER
CDTL - Cadet Large BFP LED	L35.0-LT1050 - 35W @ 1050mA ELV Low Voltage 2-Wire Dimming Electronic Driver (Leading or Trailing Edge)	120V - 277V	TRIAC Dimming @ 120V
ORDER INFO			
CDTL	L35.0-LT1050	120V - 277V	TRIAC

Example ^

Aesthetics & Options

TRIM	FINISH	COLOR TEMP	OPTIONS
Not Applicable	ORB - Oil Rubbed Bronze SN - Satin Nickel	30K - 3000K Color Temp 40K - 4000K Color Temp	Not Applicable
ORDER INFO			
Not Applicable	SN	30K	Not Applicable

Example ^

PROD	SOURCE	30K SPECS				
CDTL	L35.0	<ul style="list-style-type: none"> • 30K - 3000K Color Temp • 3200 LED Source Lumens • 91.4 LED Source Lumens Per Watt 				

NOTES

Don't see the configuration you are looking for?
Call us today at (513) 858-6004



TERONLIGHTING.COM
33 DONALD DR, FAIRFIELD, OH 45014
P: 513.858.6004 F: 513.858.6038
E: SALES@TERONLIGHT.COM

We reserve the right to revise the design components of any product due to parts availability or change in UL standards, without assuming any obligation or liability to modify any products previously manufactured, and without notice.