CITADEL W LED

Architectural Outdoor

_		
L		-
	FED	•
		•

PROJECT:	
TYPE:	
PO#:	QTY:
COMMENTS:	




FEATURES

- ADA Compliant
- Aluminum Fascia w/ Textured Black Polyester Powder Coat Finish
- Aluminum Housing w/ Textured Black Polyester Powder Coat Finish
- 4 Frosted F(1) Rated Acrylic Side Lens Panels
- LED Light Fixture
- Mounts Directly to 4" Junction Box (By Others) J-Box Centered in Fixture
- Mounting Hardware Included
- · Wet Location

LINE DRAWING

INF DRAWING NOT TO SCALE



FINISHES







Lighting Inc.

CITADEL W LED

Architectural Outdoor



PROJECT:	
TYPE:	
PO#:	QTY:
COMMENTS:	

Fixture Core

PRODUCT CODE	SOURCE/WATTAGE	VOLTAGE	DIMMING DRIVER	
CTD-W - Citadel W L20.5-ZE640 - 20.5W @ 4-Wire 0-10V Dimming Driver		120 - 277V (50/60Hz)	0-10V - 0-10V Dimming	
ORDER INFO				
CTD-W	L20.5-ZE640	120 - 277V	0-10V	
Evample ^ (may not represent a mar		12V 211V	0 101	

Example ^ (may not represent a manufacturable product)

Aesthetics & Options

TRIM	FINISH	COLOR TEMP	OPTIONS
Not Applicable ORDER INFO	AC - Antique Copper AS - Antique Silver BT - Bronze Mist SM - Matte Silver SN - Sand SW - Swedish Steel TB - Textured Black (Standard) BZ - Textured Bronze TW - Textured White	30K - 3000K Color Temp 35K - 3500K Color Temp 40K - 4000K Color Temp 50K - 5000K Color Temp	F - Fused SCV - Steel Side Covers (To Allow Up/Down Lighting) TP - Tamper Resistant Screws UL - Up Light Only DL - Down Light Only SL - Side Light Only
Not Applicable	AC	30K	F

Example ^ (may not represent a manufacturable product)

PROD	SOURCE	30K SPECS		
PROD CTD W	L20.5	30K SPECS • 30K - 3000K Color Temp • 2640 LED Source Lumens • 125.7 LED Source Lumens Per Watt		

REPLACEMENT PART	PART NO	NOTES
Lens Panel Side	3073062	
		Don't see the configuration you are looking for? Call us today at (513) 858-6004

