LAROUGE LED

Architectural Oudoor











FEATURES

- Die-Cast Aluminim Housing
- Anodized Aluminim Reflector
- LED Light Fixture
- · Glass Lense
- Mounts Directly to 4" Junction Box (By Others)
- UL Listed Wet Location
- Down Light Only


LINE DRAWING

	Α	В	С
LAROUGE-S	4.25"	6.25"	6.25"
LAROUGE-M	4.25"	8"	6.75"
LAROUGE-L	4.25"	10"	6.75"
LAROUGE-XL	4.38"	12"	6.5"





FINISHES







LAROUGE LED

Architectural Oudoor



PROJECT:	
TYPE:	
PO#:	QTY:
COMMENTS:	

Fixture Core

PRODUCT CODE	TRIM	SOURCE/WATTAGE	VOLTAGE
LRE-S	Not Applicable	L6-LED 6 Watt	120V
LRE - M		L10- LED 10 Watt	
LRE - L		L14- LED 14 Watt	
LRE - XL		L18- LED 18 Watt	
ORDER INFO			

Aesthetics & Options

DIM	FINISH	COLOR TEMP	OPTIONS
Not Applicable	BR- Bronze (Standard)	35-3500K Color Temp.	Not Applicable
	BK - Black		
ORDER INFO			

PROD	SOURCE	3500K SPECS
LRE-S	L6	600 Delivered Lumens
LRE - M	L10	• 750 Delivered Lumens
LRE-L	L14	• 900 Delivered Lumens
LRE - XL	L18	• 1050 Delivered Lumens

LACEN	

Don't see the configuration you are looking for? Call us today at (513) 858-6004



BUY AMERICAN SINCE 1979