LUNAR 1T SM C LED

Architectural Indoor








PROJECT: TYPE: PO#: QTY: COMMENTS:

FEATURES

- 0-10V Dimmable
- Acrylic Lens
- Circular Driver Box (Standard)
- Color Selectable 30K/35K/40K
- Direct Down Light
- LED Light Fixture
- Low Profile Seamless Aluminum Frame
- UL Listed Dry Location For Ceiling Mount

LINE DRAWING



FINISHES

Matte Black

Matte White

Platinum







LUNAR 1T SM C LED

Architectural Indoor

| PROJECT: | |
|-----------|------|
| TYPE: | |
| PO#: | QTY: |
| COMMENTS: | |

Fixture Core

| PRODUCT CODE | SOURCE/WATTAGE | VOLTAGE | DIMMING DRIVER | |
|---|---|-------------|----------------|--|
| LNR1T-SM-C - Lunar 1 Tier 16" Ceiling | L20.0-ZE470mA - 20.0W @ 470mA Dimming Driver | 120V - 277V | 0-10V Dimming | |
| ORDER INFO | 100 0 75470 | 400.077 | | |
| LNR1T-SM-C Example ^ | L20.0-ZE470 | 120-277V | | |

Aesthetics & Options

| TRIM | FINISH | COLOR TEMP | |
|-------------------|--|--------------------------------------|--|
| Not Applicable | BK - Matte Black MW - Matte White (Standard) PL - Platinum | SL - Color Selectable (30/35/40K) | |
| ORDER INFO | | | |
| Not Applicable | BK | SL | |

| P | ROD | SOURCE | 30K SPECS | | |
|----|----------------------|--------|---|--|--|
| LI | PROD NR1T- M-C | L20.0 | OK SPECS OUT TO SOUR COLOR TEMP OUT TO SOURCE LUMENS TO SUMMENS PER WATT OUT TO SOURCE OU | | |
| | | | | | |

| REPLACEMENT PART | PART NO | NOTES |
|------------------|---------|-------|
| | | |
| | | |
| | | |
| | | |

