

As an industrial wall pack, Caddy serves as a robust lighting solution for various applications, from illuminating loading docks to providing security lighting at the back of buildings and enhancing visibility in industrial storage areas. Its sturdy construction ensures durability in demanding environments, while its design focuses on delivering dependable and efficient illumination where it's needed most. The Caddy is the go-to choice for spaces that require powerful and reliable lighting in industrial settings, ensuring safety and functionality are never compromised.

LED Engine

- Color Temp (CCT):** 3000K, 3500K, 4000K
- CRI:** 80+ (consult factory for 90+)
- Life Expectancy:** L70 rated at 50,000+ hours
- Binning:** 3-step Macadam
- Output:** Min 1384.3 Source Lumens
Max 2307 Source Lumens


Driver

- Type:** Constant current, Class 2, 120-277 Vac, 50/60Hz
- Dimming:** 0-10V and Phase (Leading or Trailing Edge)
- Efficiency:** Min 92%
- Operating Temp:** -40°C / -40°F to 50°C / 122°F
- FCC Noise:** Meets FCC Title 47 EMC Part 15 limits

Certifications

- Location Listing:** CSA Approved Wet Location For Wall Mounting (DL Only)
- Other:** Dark Sky Compliant

Dimensions



Construction

Housing: Die-cast aluminum housing, fully gasketed, tempered clear glass lens. **Finish:** high quality polyester powder coating, various finishes. **Hardware:** Stainless steel. **Mounting:** Wall-mounted over a 4-inch junction box.

Catalog String


Fixture Core	CD	<input type="text"/>	--	<input type="text"/>	<input type="text"/>	UNIV
		1	2	3	4	5
Aesthetics & Options	<input type="text"/>	<input type="text"/>	<input type="text"/>			
	6	7	8			

Product Specifications

1 — Product Code	2 — Trim	3 — Wattage	4 — Dimming	5 — Voltage
T - CDT (<i>medium</i>) L - CDL (<i>large</i>) SQ - CDSQ (<i>square</i>)	Not Applicable	L35.0 (CDT/ZE only) L48.0 (CDL/ZE only) L12.0 (CDSQ/LT only) L20.0 (CDSQ/LT only) L26.0 (CDSQ/ZE only)	ZE - 0-10V LT - Leading/Trailing Edge	UNIV - (120V-277V)
6 — Finish	7 — CCT	8 — Options		
FBK - Fine Textured Black FBZ - Fine Textured Bronze FWH - Fine Textured White FSV - Fine Textured Silver	30K - 3000K 35K - 3500K 40K - 4000K	EB - Integral EM Battery (CDT, CDL, CDSQ) EBC - Cold Weather (-20C) EM Battery (CDT, CDL only) EBCA - Title 20 Compliant Integral EM Battery (CDT, CDL, CDSQ) F - Fused	FAL - Frosted Acrylic Lens (CDT only) MSE - External Motion Sensor PCL - Photocell (<i>specify voltage, not with CDSQ w/EB</i>) SPD - Surge Protection Device SPL - Semi Frosted Polycarbonate Lens (CDSQ only)	

Performance

Wattage	Source Lumens	Efficacy LM/W	CCT	Size
L35.0	4608	132	3000K	CDT
L48.0	6283	130		CDL
L12.0	1384.3	115.3		CDSQ
L20.0	2307	115.3		CDSQ
L26.0	2212	85		CDSQ



Polar Graph Details:

IES File Name: CADDY MD LED 35W CGL 40K.IES

Maximum Candela = 995.26 Located At Horizontal Angle = 0, Vertical Angle = 5

1 - Vertical Plane Through Horizontal Angles (0 - 180) (Through Max. Cd.)

2 - Horizontal Cone Through Vertical Angle (5) (Through Max. Cd.)

BUG Rating: B1-U0-G0