

Faultless

Architectural Indoor



True to its name, Faultless delivers impeccable performance as an indoor ceiling light tailored for multifamily and hospitality settings. Its design leans towards serving practical and utilitarian purposes, making it an ideal choice for utility rooms and spaces where functionality takes precedence. Offering consistent and even illumination, Faultless stands as the go-to solution for areas demanding reliable and straightforward lighting without the frills. Efficient, dependable, and truly 'faultless' in its delivery.

LED Engine

- Color Temp (CCT):** 3000K, 3500K, 4000K
- CRI:** 80+ (consult factory for 90+)
- Life Expectancy:** L70 rated at 50,000+ hours
- Binning:** 3-step Macadam
- Output:** Min 979 Delivered Lumens
Max 2879 Delivered Lumens


Driver

- Type:** Constant current, Class 2, 120-277 Vac, 50/60Hz
- Dimming:** 0-10V
- Efficiency:** Min 92%
- Operating Temp:** -40°C / -40°F to 50°C / 122°F
- FCC Noise:** Meets FCC Title 47 EMC Part 15 limits

Certifications

- Location Listing:** Damp Location Rated for Ceiling Mounting
- Other:** ADA Compliant

Dimensions



Construction

Mounting Pan: stamped steel. **Diffuser:** white acrylic. **Finish:** high quality polyester powder coating, various finishes. **Mounting:** wall-mounted over a 4inch junction box.



Catalog String

Fixture Core

FS

1

2

3

ZE

4

UNIV

5

Aesthetics & Options

6

7

8


Product Specifications

1 — Product Code	2 — Trim	3 — Wattage	4 — Dimming	5 — Voltage
11 - FS11 14 - FS14 19 - FS19	Not Applicable	L13.5 L17.0 L20.5 L28.5	ZE - 0-10V	UNIV - (120V-277V)

6 — Finish	7 — CCT	8 — Options	
FBK - Fine Textured Black FBZ - Fine Textured Bronze FWH - Fine Textured White FSV - Fine Textured Silver	30K - 3000K 35K - 3500K 40K - 4000K	ALP - Aluminum Mount Pan BB - Back Box EB/BB - Back Box Integral EM Battery F - Fused SPD - Surge Protection Device TP - Tamper-Proof Screw Set	STC12-WH - 12" Stem and Canopy Kit STC24-WH - 24" Stem and Canopy Kit STC36-WH - 36" Stem and Canopy Kit STC48-WH - 48" Stem and Canopy Kit WAL - White Acrylic Lens WPL - White Polycarbonate Lens

Performance

Wattage	Delivered Lumens	Efficacy LM/W	CCT
L13.5	979	65.3	3000K
L17.0	1364	73.2	
L20.5	1643	68.2	
L28.5	2123	74.5	



Polar Graph Details:

IES File Name: FS-L13.0 ZE560-30K. IES

Maximum Candela = 278 Located At Horizontal Angle = 0, Vertical Angle = 0

1 - Vertical Plane Through Horizontal Angles (0 - 180) (Through Max. Cd.)

2 - Horizontal Cone Through Vertical Angle (0) (Through Max. Cd.)