




Designed for resilience, Heritage stands as a bastion of durability in the world of lighting. As an outdoor wall or ceiling bulkhead fixture, it thrives in challenging environments, particularly suited for industrial settings and high-use scenarios. Its robust construction makes it impact-resistant, ensuring it remains unfazed by the rigors of daily wear and tear. For locations demanding heavy-duty performance without compromising on aesthetics, Heritage is the epitome of strength, reliability, and steadfastness. Ideal for spaces where endurance meets elegance.

LED Engine

Color Temp (CCT): 3000K, 3500K, 4000K
CRI: 80+ (consult factory for 90+)
Life Expectancy: L70 rated at 50,000+ hours
Binning: 3-step Macadam
Output: Min 1896 Source Lumens
 Max 3100 Source Lumens


Driver

Type: Constant current, Class 2, 120-277 Vac, 50/60Hz
Dimming: 0-10V
Efficiency: Min 92%
Operating Temp: -40°C / -40°F to 50°C / 122°F
FCC Noise: Meets FCC Title 47 EMC Part 15 limits

Certifications

Location Listing: Wet Location for Wall and Ceiling Mounting
Other: Buy America Compliant
 ADA - HRTS Only

Dimensions



Construction

Housing: die-cast marine grade aluminum. **Trim:** injection-molded polycarbonate frame, with injection molded white luminous lens. **Finish:** high quality polyester powder coating, various finishes. **Hardware:** Stainless steel. **Mounting:** wall-mount over 4-inch junction box.

Catalog String

Fixture Core					UNV
	1	2	3	4	5
Aesthetics & Options					
	6	7	8		

Product Specifications

1 — Product Code	2 — Trim	3 — Wattage	4 — Dimming	5 — Voltage
Round - HRT	RNG	L20.0 - (HRTS only)	ZE - 0-10V	UNV - (120V-277V)
Shallow - HRTS	CRS	L20.5 - (HRT only)		
	EYE	L24.5 - (HRT only)		
		L30.0 - (HRT only)		

6 — Finish	7 — CCT	8 — Options
BK - Matte Black	30K - 3000K	EB - Integral EM Battery (HRT Only) TP - Tamper Resistant Screws
BZ - Matte Bronze	35K - 3500K	F - Fused
WH - Matte White	40K - 4000K	PCL - Photocell (<i>specify voltage</i>) (HRT Only)
		SPD - Surge Protection Device (HRT Only)

Performance

Wattage	Source Lumens	Efficacy LM/W	CCT	Size
L20.0	3280	160	3000K	Shallow
L20.5	3100	151		Round
L24.5	3969	162		Round
L30.0	4907	164		Round