

# Sure Shot

Architectural Indoor



Meticulously crafted for sophisticated vanity settings, Sure Shot offers a fusion of elegance and precise illumination. Optimal for multifamily residences, luxury hotels, and other discerning spaces, its design ensures that every reflection is showcased in the best light. What sets it apart is its availability in both deep and narrow configurations, allowing for a tailored lighting experience to suit varied aesthetic preferences. For those venues and residences seeking a lighting solution that melds adaptability with sheer elegance, Sure Shot rises as the distinguished choice.

## LED Engine

- Color Temp (CCT):** 3000K, 3500K, 4000K
- CRI:** 80+ (consult factory for 90+)
- Life Expectancy:** L70 rated at 50,000+ hours
- Binning:** 3-step Macadam
- Output:** Min 4970 Source Lumens  
Max 7161 Source Lumens

## Driver



- Type:** Constant current, Class 2, 120-277 Vac, 50/60Hz
- Dimming:** 0-10V and Phase (Leading or Trailing edge)
- Efficiency:** Min 92%
- Operating Temp:** -40°C / -40°F to 50°C / 122°F
- FCC Noise:** Meets FCC Title 47 EMC Part 15 limits

## Certifications



- Location Listing:** Damp Location Rated for Wall Mounting
- Other:** Buy America Compliant

## Dimensions

MODEL SIZE	L
SURE SHOT DOUBLE LED 24"	24-3/4"
SURE SHOT DOUBLE LED 36"	36-3/4"



MODEL SIZE	LENGTH (L)
SURE SHOT LED 18"	18-3/4"
SURE SHOT LED 24"	24-3/4"
SURE SHOT LED 36"	36-3/4"



## Construction

**Mounting Pan:** Die-formed steel with high-reflectance white finish. **Diffuser:** luminous white acrylic. **End Caps:** Stamped steel end caps. **Finish:** high quality polyester powder coating, various finishes. **Mounting:** Wall mounted over 4 inch junction box.



## Catalog String

Fixture Core

SS

1

2

3

4

UNIV

5

Aesthetics & Options

6

7


8

## Product Specifications

1 — Product Code	2 — Trim	3 — Wattage	4 — Dimming	5 — Voltage
18 - SS18	N (Narrow)	L17.0 (18/24/N only)	ZE - 0-10V	UNIV - (120V-277V)
24 - SS24	D (Deep)	L17.9 (18/N/LT only)	LT - Leading & Trailing Edge	
36 - SS36		L34.0 (24/D/ZE only)		
48 - SS48		L49.0 (48/D/ZE only)		
		L35.7 (36/N/ZE only)		
		L59.5 (36/D/ZE only)		
6 — Finish	7 — CCT	8 — Options		
FBK - Fine Textured Black	30K - 3000K	2WS - 2 Way Pull Switch		
FBZ - Fine Textured Bronze	35K - 3500K	CO - Convenience Outlet		
FWH - Fine Textured White	40K - 4000K	F - Fused		
FSV - Fine Textured Silver				

## Performance

Wattage	Source Lumens	Efficacy LM/W	CCT	Size
L17.0	2505	147.4	3000K	18, 24
L17.9	2386	133.3		18
L34.0	4970	146.2		24
L49.0	7161	146.1		48
L35.7	5217	146.1		36
L59.5	8695	146.1		36



### Polar Graph Details:

IES File Name: SSD24-L34.0-ZE1000-30K.IES

Maximum Candela = 803 Located At Horizontal Angle = 0, Vertical Angle = 45

# 1 - Vertical Plane Through Horizontal Angles (0 - 180) (Through Max. Cd.)

# 2 - Horizontal Cone Through Vertical Angle (45) (Through Max. Cd.)