


Torino

Architectural Indoor



A paragon of elegance and versatility, Torino offers upscale illumination for discerning spaces. Uniquely designed for vanity applications, it can be seamlessly mounted both horizontally and vertically, catering to diverse aesthetic and functional requirements. Its luminous grace enhances multifamily residences, luxury hotels, and other prestigious environments. The meticulously engineered glow ensures that every detail, whether reflected in a mirror or showcased in a room, is brilliantly lit. For spaces aiming for a blend of luxury and adaptability in lighting, Torino is the gold standard.

LED Engine

- Color Temp (CCT):** 3000K, 3500K, 4000K
- CRI:** 80+ (consult factory for 90+)
- Life Expectancy:** L70 rated at 50,000+ hours
- Binning:** 3-step Macadam
- Output:** Min 1470 Source Lumens
Max 2981 Source Lumens


Driver

- Type:** Constant current, Class 2, 120-277 Vac, 50/60Hz
- Dimming:** 0-10V and phase (trailing edge)
- Efficiency:** Min 92%
- Operating Temp:** -40°C / -40°F to 50°C / 122°F
- FCC Noise:** Meets FCC Title 47 EMC Part 15 limits

Certifications

- Location Listing:** Damp for Wall and Ceiling Mounting
- Other:** ADA Compliant
Buy America Compliant

Dimensions



Construction

Mounting Plate: Die-formed steel. **Trim:** die-formed steel with luminous impact resistant diffuser. **Finish:** high quality polyester powder coating, various finishes. **Mounting:** Wall or Ceiling



Catalog String


Fixture Core	TNO	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	UNIV
		1	2	3	4		5
Aesthetics & Options		<input type="text"/>	<input type="text"/>	<input type="text"/>			
		6	7	8			

Product Specifications

1 — Product Code	2 — Trim	3 — Wattage	4 — Dimming	5 — Voltage
24 - TNO24 36 - TNO36 48 - TNO48	STD (Blank) TWC	L20.1 (24/ZE only) L27.2 (36/ZE only) L34.7 (48/ZE only) L38.3 (48/ZE only)	ZE - 0-10V TE - Trailing Edge	UNIV - (120V-277V)
6 — Finish	7 — CCT	8 — Options		
FBK - Fine Textured Black FBZ - Fine Textured Bronze FWH - Fine Textured White FSV - Fine Textured Silver	30K - 3000K 35K - 3500K 40K - 4000K	EB - Integral EM Battery (36/48 only) F - Fused JBC - Junction Box Cover TP - Tamper Resistant Screws		

Performance

Wattage	Source Lumens	Efficacy LM/W	CCT	Size
L20.1	1474	64	3000K	24/ZE
L27.2	2303	70		36/ZE
L38.3	2981	66		48/ZE



Polar Graph Details:

IES File Name: TORINO LED 2FT 20.1W 30K.IES

Maximum Candela = 282 Located At Horizontal Angle = 0, Vertical Angle = 115

1 - Vertical Plane Through Horizontal Angles (0 - 180) (Through Max. Cd.)

2 - Horizontal Cone Through Vertical Angle (115) (Through Max. Cd.)