ASTRO PD BFP LED 20"

Architectural Indoor















FEATURES

- Steel Housing with White Finish
- Inner Shade: Off White Decorative Fiber Linen
- Outer Shade: Semi-Clear Silver Decorative Fiber Linen


PROJECT: TYPE: PO#:

COMMENTS:

- Bottom Lens: White High Transmission Acrylic Lens
- ETL/cETL Listed Damp Location
- Energy Star
- Mounts Directly to Surface w/ Two Wall Anchors
- LED Light Fixture
- UL/cUL Listed

LINE DRAWING

QTY:



FINISHES

Brushed Nickel





ASTRO PD BFP LED 20"

Architectural Indoor

| ofM7e. | | _ |
|--------|-----|---|
| | LED | 1 |









| . (ii). | 10 |
|---------|----|
| LIETED | 13 |

Fixture Core

| PRODUCT CODE | SOURCE/WATTAGE | VOLTAGE | DIMMING DRIVER |
|----------------------------------------------|----------------------------------------|-------------|----------------|
| AO20PD - Astro Pendant 20" (With 6" Stem) | L35.0-1050 - (1) 35.0W @ 1050mA | 120V - 277V | Not Applicable |
| | | | |
| ORDER INFO | | | |
| AS20PD Example ^ | L35.0-1050 | 120/277V | Not Applicable |

PROJECT: TYPE:

COMMENTS:

QTY:

PO#:

Aesthetics & Options

| TRIM | FINISH | COLOR TEMP | OPTIONS |
|-------------------|---------------------------------------------|------------------------------------------------------------------|----------------|
| Not Applicable | BN - Brushed Nickel (Standard) | 30K - 3000K Color Temp. 40K - 4000K Color Temp. | Not Applicable |
| ORDER INFO | | | |
| Not Applicable | BN | 30K | Not Applicable |

| PROD | SOURCE | 30K SPECS | | |
|--------|--------|---------------------------------------------------------------------------------------------------|--|--|
| AO20PD | L35.0 | OK SPECS OUT TO SOUR COLOR TEMP Isou LED Source Lumens Ioo LED Source Lumens Per Watt Out CRI | | |
| | | | | |

| REPLACEMENT PART | PART NO |
|------------------|---------|
|------------------|---------|

L70 >35,000 hrs

Minimum Starting Temperature = -20 Degrees C

