DUNLOP LED 36"

Architectural Indoor

/CN	
(.)H	
(N)?	









FEATURES

- Aluminum Housing w/ Hi-Reflectance White Powder Coat Finish
- Aluminum LED Mount Plate
- CSA Listed Damp Location For Surface Mount
- Die-Formed Cold-Rolled Steel End Caps w/ Brushed Nickel Plated Finish
- Emergency Battery Available
- LED Light Fixture
- · Luminous White Acrylic Diffuser
- Mounts Directly to Surface w/ Two Wall Anchors (Not Included)
- Vandal Resistant



LINE DRAWING 5 3/4



FINISHES

Antique Copper Textured Black







Matte





Textured White

Antique

Silver

For RAL Colors & Custom Match -**Contact Teron** Lighting Inc.





TERONLIGHTING.COM

DUNLOP LED 36"

Architectural Indoor



PROJECT:	
TYPE:	
PO#:	QTY:
COMMENTS:	

Fixture Core

PRODUCT CODE	SOURCE/WATTAGE	VOLTAGE	DIMMING DRIVER	
DP36 - Dunlop 36"	L23.2-LT700 - 23.2W @ 700mA ELV Dimming Driver	120-277V	LT Drivers are dimmable @120V	
	L23.2-ZE700 - 23.2W @ 700mA 0-10V Dimming Driver		ZE Drivers are dimmable 120-277V	
	L30.0-LT875 - 30W @ 875mA ELV Dimming Driver			
ORDER INFO	L30.0-ZE875 - 30W @ 875mA 0-10V Dimming Driver			
DP36	L23.2-TE700	120-277V	Not Applicable	
Example ^				

Aesthetics & Options

TRIM	FINISH	COLOR TEMP	OPTIONS
Not Applicable	AC - Antique Copper AS - Antique Silver BT - Bronze Mist BN - Brushed Nickel Plate (Standard) SM - Matte Silver SN - Sand SW - Swedis Steel TB - Texture Black BZ - Texture Bronze TW - Texture White	35K - 3500K Color Temp 40K - 4000K Color Temp	EB5 - 5W Intergral EM Battery F - Fused TP - Tamper Resistant
DRDER INFO			
Not Applicable	BN	30K	EB5

- 1				
PROD	SOURCE	30K SPECS		
DP36	L23.2	30K - 3000K Color Temp 2496LED Source Lumens 107 LED Source Lumens Per Watt		
	L30.0	30K - 3000K Color Temp 3028 LED Source Lumens 101 LED Source Lumens Per Watt		

REPLACEMENT PART	PART NO	NOTES
36" White Acrylic LED Lens Assembly	38219	Don't see the configuration you are looking for? Call us today at (513) 858-6004

