HERITAGE SHALLOW CRS LED

Architectural Outdoor








PROJECT: TYPE: PO#: QTY: COMMENTS:

FEATURES

- 100V 277V
- CSA Listed Wet Location For Wall or Ceiling Mount
- Die-Cast, Marine Grade Aluminum Housing
- EPMD Ribbed / Foam Rubber Gasketing
- Injection Molded Polycarbonate Fascia w/ Weep Holes
- Junction Box Pattern on Housing For Easy Mounting
- Translucent White Injection Molded Lens Frame
- UV-Stabilizing Polycarbonate Diffuser

LINE DRAWING



FINISHES

For RAL Colors & Custom Match -**Contact Teron** Lighting Inc.





HERITAGE SHALLOW CRS LED

Architectural Outdoor



Ш	rec	LUI	aı	Οu	tuu	U

Fixture Core

PROJECT:	
TYPE:	
PO#:	QTY:
COMMENTS:	·

PRODUCT CODE	SOURCE/WATTAGE	VOLTAGE	DIMMING DRIVER
HRTS - Heritage Shallow	L20.0- ZE700 - 20 Watts @ 20 700mA (0-10V Dimming Driver)	100 - 277V (50 / 60Hz)	0-10V Dimming
ORDER INFO HRTS	L20.0-ZE700	100 - 277V	Not Applicable

Example ^ (may not represent a manufacturable product)

Aesthetics & Options

TRIM	FINISH	COLOR TEMP	OPTIONS
CRS	BK - Matte Black BZ - Matte Bronze WH - Matte White TI - Matte Titanium	30K - 3000K Color Temp 35K - 3500K Color Temp 40K - 4000K Color Temp 50K - 5000K Color Temp	FRL- Frosted Ribbed Lens TP - Tamper Resistant Screws
ORDER INFO	BK	27K	EB51

Example ^ (may not represent a manufacturable product)

PROD	SOURCE	30K SPECS		
HRTS	L20.0	30K SPECS 30K - 3000K Color Temp 3398.5 LED Source Lumens 169.9 LED Source Lumens Per Watt		

REPLACEMENT PART	PART NO	NOTES
White Ribbed Polycarbonate Diffuser	3408360	White Ribbed is standard lens.
Frosted Ribbed Polycarbonate Diffuser	3408362	Don't see the configuration you are looking for? Call us today at (513) 858-6004

