

SILHOUETTE RD LG LED

Architectural Indoor



PROJECT:	
TYPE:	
PO#:	QTY:
COMMENTS:	



FEATURES

- [Stem and Canopy Kits Available](#)
- Steel Mounting Pan w/ Hi-Reflectance White Powder Coat Finish
- Aluminum Mounting Pan w/ Hi-Reflectance White Powder Coat Finish (For L30.0 Only)
- Luminous White Acrylic Diffuser W/ Decorative Fabric Trim (Gold Vein, Mocha, Natural Linen, And White Linen)
- Brushed Nickel Vinyl Has a Luminous White Acrylic Diffuser w/ Solid Vinyl Material Providing Down Light Only
- Mounts Directly to 4" Junction Box (By Others)
- CSA Listed Dry Location For Ceiling Mount Only
- Emergency Battery Available
- LED Light Fixture
- Mounting Hardware Included



LINE DRAWING

LINE DRAWING NOT TO SCALE



FINISHES


Brushed Nickel Vinyl



Gold Vein




Mocha



Natural Linen



White Linen



For RAL Colors & Custom Match - Contact Teron Lighting Inc.

SILHOUETTE RD LG LED

Architectural Indoor



Fixture Core

PROJECT:	
TYPE:	
PO#:	QTY:
COMMENTS:	

PRODUCT CODE	TRIM	SOURCE/WATTAGE	DIMMING DRIVER
SHRL19 - Silhouette RD LG	Not Applicable	L21.0 - 21.0W L28.5 - 28.5W	ZE - 0-10V Dimming
ORDER INFO			
SHRL19 Example ^	L21.0-ZE550	L21	ZE

Aesthetics & Options

VOLTAGE	FINISH	COLOR TEMP	OPTIONS
UNV (50 / 60Hz)	GVN - Gold Vein MOC - Mocha NLN - Natural Linen BNV - Brushed Nickel Vinyl WLN - White Linen	30K - 3000K Color Temp 35K - 3500K Color Temp 40K - 4000K Color Temp 50K - 5000K Color Temp	BB - Back Box EBW/BB - Bodine BSL26 - Up to 5.1W Emergency Illumination With LEDs (Back Box Required)* F - Fused SP - Surge Protector STC12-WH - 12" Stem and Canopy Kit STC24-WH - 24" Stem and Canopy Kit STC36-WH - 36" Stem and Canopy Kit STC48-WH - 48" Stem and Canopy Kit
ORDER INFO			
Not Applicable Example ^	GVN	30K	BB

PROD	SOURCE	30K SPECS	30K SPECS	30K SPECS
SHRL19	L21.0	<ul style="list-style-type: none"> TNV / NLN / GVN 80 CRI Typ. 30K - 3000K Color Temp 3100 LED Source Lumens 151 LED Source Lumens Per Watt 	<ul style="list-style-type: none"> MOC Fabric 80 CRI Typ. 30K - 3000K Color Temp 3100 LED Source Lumens 151 LED Source Lumens Per Watt 1450 Delivered LED Lumens 60.1 Delivered LED Lumens Per Watt 	<ul style="list-style-type: none"> WMS Fabric 80 CRI Typ. 30K - 3000K Color Temp 3100 LED Source Lumens 151 LED Source Lumens Per Watt 2331 Delivered LED Lumens 96.7 Delivered LED Lumens Per Watt
	L28.5	<ul style="list-style-type: none"> 80 CRI Typ. 30K - 3000K Color Temp 4100 LED Source Lumens 144 LED Source Lumens Per Watt 	<ul style="list-style-type: none"> 80 CRI Typ. 30K - 3000K Color Temp 4100 LED Source Lumens 144 LED Source Lumens Per Watt 55.5 Delivered LED Lumens Per watt 	<ul style="list-style-type: none"> 80 CRI Typ. 30K - 3000K Color Temp 4100LED Source Lumens 144 LED Source Lumens Per Watt 92.4 Delivered LED Lumens Per watt

REPLACEMENT PART	PART NO	NOTES
19" Brushed Nickel Vinyl	3071092	Don't see the configuration you are looking for? Call us today at (513) 858-6004
19" Gold Vein	3071086	
19" Mocha	3071087	
19" Natural Linen	3071091	
19" White Linen	3071089	



TERONLIGHTING.COM
33 DONALD DR, FAIRFIELD, OH 45014
P: 513.858.6004 F: 513.858.6038
E: SALES@TERONLIGHT.COM



We reserve the right to revise the design components of any product due to parts availability or change in UL standards, without assuming any obligation or liability to modify any products previously manufactured, and without notice.

SEND CUT-SHEET

SILHOUETTE RD LG LED

Architectural Indoor



Fixture Core

PROJECT:	
TYPE:	
PO#:	QTY:
COMMENTS:	

PRODUCT CODE	TRIM	SOURCE/WATTAGE	DIMMING DRIVER
SHRL19 - Silhouette RD LG	Not Applicable	L37.5 - L37.5W	ZE - 0-10V Dimming
ORDER INFO			
SHRL19 Example ^	L37.5-ZE1050	120-277V	Not Applicable

Aesthetics & Options

VOLTAGE	FINISH	COLOR TEMP	OPTIONS
UNV (50 / 60Hz)	GVN - Gold Vein MOC - Mocha NLN - Natural Linen BNV - Brushed Nickel Vinyl WLN - White Linen	30K - 3000K Color Temp 35K - 3500K Color Temp 40K - 4000K Color Temp 50K - 5000K Color Temp	BB - Back Box EBW/BB - Bodine BSL26 - Up to 5.1W Emergency Illumination With LEDs (Back Box Required)* F - Fused SP - Surge Protector STC12-WH - 12" Stem and Canopy Kit STC24-WH - 24" Stem and Canopy Kit STC36-WH - 36" Stem and Canopy Kit STC48-WH - 48" Stem and Canopy Kit TP - Tamper-Proof Screw Set
ORDER INFO			
Not Applicable Example ^	GVN	30K	BB

PROD	SOURCE	30K SPECS	30K SPECS	30K SPECS
SHRL19	L37.5	<ul style="list-style-type: none"> TNV / NLN / GVN 80 CRI Typ. 30K - 3000K Color Temp 4845 LED Source Lumens 135.5 LED Source Lumens Per Watt 	<ul style="list-style-type: none"> MOC Fabric 80 CRI Typ. 30K - 3000K Color Temp 4845 LED Source Lumens 135.5 LED Source Lumens Per Watt 2099 Delivered LED Lumens 58.7 Delivered LED Lumens Per Watt 	<ul style="list-style-type: none"> WMS Fabric 80 CRI Typ. 30K - 3000K Color Temp 4845 LED Source Lumens 135.5 LED Source Lumens Per Watt 3581 Delivered LED Lumens 100 Delivered LED Lumens Per Watt

REPLACEMENT PART	PART NO	NOTES
19" Brushed Nickel Vinyl	3071092	Don't see the configuration you are looking for? Call us today at (513) 858-6004
19" Gold Vein	3071086	
19" Mocha	3071087	
19" Natural Linen	3071091	
19" White Linen	3071089	



TERONLIGHTING.COM
 33 DONALD DR, FAIRFIELD, OH 45014
 P: 513.858.6004 F: 513.858.6038
 E: SALES@TERONLIGHT.COM



We reserve the right to revise the design components of any product due to parts availability or change in UL standards, without assuming any obligation or liability to modify any products previously manufactured, and without notice.

SEND CUT-SHEET