

SPIRIT PANEL 2X2 LED

Architectural Indoor



PROJECT:	
TYPE:	
PO#:	QTY:
COMMENTS:	




FEATURES

- 0-10V Dimmable (10%-100%)
- 120 Degree Beam Angle
- 5 Year Warranty
- Aluminum Frame In White Finish, Steel Die-Formed Back Enclosure
- cULus Listed Damp Location For Ceiling Mount
- IC Rated For Insulated Ceilings
- Integral Earthquake Clips for Secure Attachment
- LED Backlit Flat Panel
- DesignLights Consortium® (DLC) Premium Listed
- Linear Driver Integrated Into Side of Panel
- Operating Temp Range -20 Degrees C to 35 Degrees C
- PMMA Lenses Over LEDs, PS Diffuser
- Integral Backup Battery Available
- RoHS, FCC
- Surface Mount and Suspension Mount Cable Kit Accessories Available
- Weight: 4.41 lbs

LINE DRAWING

LINE DRAWING NOT TO SCALE



FINISHES

Matte White



SPIRIT PANEL 2X2 LED

Architectural Indoor



Fixture Core

PROJECT:	
TYPE:	
PO#:	QTY:
COMMENTS:	

PRODUCT CODE	TRIM	SOURCE/WATTAGE	VOLTAGE
FPE2X2-P (Flat Panel 2' x 2')	Not Applicable	L30.0 L36.0	UNV (120 - 277V) 347 (347V)
ORDER INFO			
FPE2X2 Example ^	Not Applicable	L30.0	UNV

Aesthetics & Options

DIM	FINISH	COLOR TEMP	OPTIONS
ZE (0-10V Dimming)	MW - Matte White (Standard)	835K - 80 CRI 3500K Color Temp. 840K - 80 CRI 4000K Color Temp. 850K - 80 CRI 5000K Color Temp.	2CA - Two Cable Suspension Mounting Kit (See Install Instructions) 4CA - Four Cable Suspension Mounting Kit (See Install Instructions) EB - Integral Emergency Battery REC - Recessed Flange Kit SRK - Surface Mounting Kit (See Install Instructions)
ORDER INFO			
ZE Example ^	MW	835K	2CA

Actual production units may vary from the values reported here by up to +/-10%

PERFORMANCE (DELIVERED LUMENS)						
WATTAGE	80 CRI 3500K	LUMENS/WATT	80 CRI 4000K	LUMENS/WATT	80CRI 5000K	LUMENS/WATT
L30.0	3750	125	3825	128	3900	130
L36.0	4500	125	4590	128	4680	130

ELECTRICAL DATA

WATTAGE	120V	208V	240V	277V	347V	480V
L30.0	0.25A	0.14A	0.13A	0.11A	0.09A	N/A
L36.0	0.3A	0.17A	0.15A	0.13A	0.10A	N/A

REPLACEMENT PART	PART NO	NOTES



TERONLIGHTING.COM
 33 DONALD DR, FAIRFIELD, OH 45014
 P: 513.858.6004 F: 513.858.6038
 E: SALES@TERONLIGHT.COM

We reserve the right to revise the design components of any product due to parts availability or change in UL standards, without assuming any obligation or liability to modify any products previously manufactured, and without notice.