VICEROY W LED 36"

Architectural Outdoor





FEATURES


- ADA Compliant
- Aluminum Fixture w/ Matte Silver Powder Coat Finish

PROJECT: TYPE: PO#:

COMMENTS:

- Aluminum Mounting Plate Mounts to Wall Surface (Centered Over Conduit)
- CSA Listed Wet Location For Wall Mount
- Dimmable @ 120-277V
- Estimated Lumen Depreciation (TM-21) 70% of Initial Lumens (L70) @ 90,000 Hours
- Integral Surge Protector
- Leading or Trailing edge or 0-10V Dimming Avaialble
- LED Light Fixture
- Requires a 1/2" Watertight Conduit Connector (Not Included)
- White Acrylic Lens
- 0-10V Dimming

LINE DRAWING



FINISHES Antique Antique Bronze Matte Sand Swedish Copper Steel Silver Mist Silver Textured Textured Textured Black Bronze White For RAL Colors & Custom Match -**Contact Teron** Lighting Inc.



 TERONLIGHTING.COM

 33 DONALD DR, FAIRFIELD, OH 45014

 P: 513.858.6004
 F: 513.858.6038

 E: SALES@TERONLIGHT.COM



We reserve the right to revise the design components of any product due to parts availability or change in UL standards, without assuming any obligation or liability to modify any products previously manufactured, and without notice. 1

QTY:

VICEROY W LED 36"

Architectural Outdoor

£. 🕀 📼

	PROJECT:	
	TYPE:	
	PO#:	QTY:
	COMMENTS:	

Fixture Core PRODUCT CODE	SOURCE/WATTAGE	VOLTAGE	DIMMING DRIVER
VCYV36 - Viceroy W 36"	L30.0-ZE880 - 30.0W LED Strip(s) @ 880mA Line Voltage 4-Wire Dimming Driver (Dimmable 0 - 10V)	120-277V	0-10V Dimming
ORDER INFO			
VCYW36	L30.0-ZE880	120-277V	Not Applicable

Aesthetics & Options

TRIM Not Applicable		FINISHAC - Antique Copper AS - Antique SilverSW - Swedish SteelBT - Bronze Mist BZ - Textured BronzeTB - Textured BlackBX - Matte Silver (Standard)TW - Textured 		COLOR TEMP 30K - 3000K Color Temp 35K - 3500K Color Temp 40K - 4000K Color Temp 50K - 5000K Color Temp			OPTIONS Not Applicable		
ORDER INFO									
Not Applicable Example ^		SM		ЗОК			Not Applicable		
PROD	SOURCE 3	OK SPECS							
VCYW36	L30.0 •	30K - 3000K Color Temp 2907 LED Delivered Lumens 96.9 LED Delivered Lumens Per Watt							

NOTES 3' Lens Assembly 3059060 Don't see the configuration you are looking for? Call us today at (513) 858-6004



TERONLIGHTING.COM 33 DONALD DR, FAIRFIELD, OH 45014 P: 513.858.6004 F: 513.858.6038 E: SALES@TERONLIGHT.COM



We reserve the right to revise the design components of any product due to parts availability or change in UL standards, without assuming any obligation or liability to modify any products previously manufactured, and without notice.