

# KINSINTON BK 52"

Indoor Ceiling Fan

|           |      |
|-----------|------|
| PROJECT:  |      |
| TYPE:     |      |
| PO#:      | QTY: |
| COMMENTS: |      |

## FEATURES



- UL Listed for Indoor Dry
- AC Motor
- Lead Wire Length of 78"
- Includes 6" Ceiling Rod
- Over All Height 15.8"
- 4 Blades @ Pitch 10°
- WC-6 Wall Control 3 Speed Forward/Reverse (Included)
- Dual Mounting with Max Stem Tilt of 25°
- Mounting Weight 17.2 lbs
- Minimum Distance - Blade to floor 7 ft
- LED Light Fixture

| AIRFLOW<br>Cubic Ft. Per<br>Minute on High | RPM<br>Revolutions Per-<br>Minute on High | POWER USAGE<br>Watts on High (Ex-<br>cluding Lights) |
|--|---|--|
| 3253                                       | 167                                       | 47.65  |

| PRODUCT CODE                             | LENS                     | WATTAGE                   | LIGHT SOURCE                  |
|--|--------------------------|---------------------------|-------------------------------|
| <b>KINS52- Kinsinton<br/>52" 4 Blade</b> | <b>FG- Frosted Glass</b> | <b>L48.0 - 48W (HIGH)</b> | <b>1 x 18W LED (Included)</b> |
| ORDER INFO                               |                          |                           |                               |
|  |                          |                           |                               |

Example ^ (may not represent a manufacturable product)

| VOLTAGE           | FINISH           | BLADE FINISH     | OPTIONS  |
|-------------------|------------------|------------------|--|
| <b>120 - 120V</b> | <b>BK- Black</b> | <b>BK- Black</b> | <b>RD12 - 12" Downrod<br/>RD24 - 24" Downrod<br/>RD36 - 36" Downrod<br/>RD48 - 48" Downrod</b> |
| ORDER INFO        |                  |                  |  |
|                   |                  |                  |  |



TERONLIGHTING.COM  
 33 DONALD DR, FAIRFIELD, OH 45014  
 P: 513.858.6004 F: 513.858.6038  
 E: SALES@TERONLIGHT.COM

Rev 07142022

We reserve the right to revise the design components of any product due to parts availability or change in UL standards, without assuming any obligation or liability to modify any products previously manufactured, and without notice.